



JN0-740^{Q&As}

ACX, Specialist (JNCIS-ACX)

Pass Juniper JN0-740 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-740.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You have correctly changed your NetScreen Remote Client Security Policy, but it does not seem to be active. What two (2) actions should you take?

- A. If the policy is already active, right click on the NetScreen Remote icon and select "Reload Security Policy"
- B. If the policy is not active then right click on the NetScreen Remote icon and Select "Activate Security Policy"
- C. If the policy is not active, select the File menu from the Security policy editor and Select "Activate Security Policy"
- D. If the policy is already active, select the File menu from the Security policy editor and then select "Reload Security Policy"

Correct Answer: AB

QUESTION 2

You are creating route-based VPNs on a NS208. When creating your 101st interface, you receive an error message and are prevented from creating additional tunnel interfaces.

What would cause this problem?

- A. There is a limit of 100 tunnel interfaces per zone.
- B. There is a limit of 100 tunnel interfaces per NS208.
- C. There is a limit of 100 tunnel interfaces per virtual router.
- D. Acquire a license key to increase the number of tunnel interfaces that can be created.

Correct Answer: B

QUESTION 3

In the command `save config from tftp 1.1.abcd.cfg merge`, which function does the merge parameter specify?

- A. The config file from the TFTP server will replace the configuration in RAM.
- B. The config file from the TFTP server will replace the startup configuration file in internal flash.
- C. The merge parameter is not valid for TFTP files, it is only valid for configuration files stored in internal flash.
- D. The config file from the TFTP server will be combined with the configuration file in RAM and the combined result will be saved in internal flash.

Correct Answer: D

QUESTION 4



If all interfaces are configured for route mode, what will be modified by the ScreenOS device when traffic travels from the trust zone to the untrust zone?

- A. source IP
- B. source port
- C. source MAC
- D. destination IP
- E. destination port

Correct Answer: C

QUESTION 5

Which command is used to avoid IP Fragmentation when configuring IPSec on a NetScreen device?

- A. set flow
- B. set tcp-mss flow
- C. set flow tcp-mss
- D. set mss-flow size

Correct Answer: C

[Latest JN0-740 Dumps](#)

[JN0-740 Practice Test](#)

[JN0-740 Study Guide](#)