

NCP-MCI-5.20^{Q&As}

Nutanix Certified Professional - Multi cloud Infrastructure (NCP-5.20)

Pass Nutanix NCP-MCI-5.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/ncp-mci-5-20.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Nutanix Official Exam Center

Instant Download After Purchase

- 100% Money Back Guarantee
- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

An administrator wants to have a VM on an AHV cluster with access to multiple VLANs. What is the most efficient way to achieve this?

- A. Update a vNIC on the VM to operate in trunked mode for all desired VLANs.
- B. Create a network in AHV associated with all those VLANs on all hosts.
- C. Use SFPs that allow the needed VLANs.
- D. Use one vNIC per VLAN for the VM.

Correct Answer: A

QUESTION 2

How should an administrator correct an SSL error while connecting to a Nutanix Cluster?

- A. renew ssl self signed
- B. AD group policy
- C. add cert to trusted in local system
- D. create new cert from AD CA Authority

Correct Answer: A

QUESTION 3

Microsegmentation was recently enabled in a Nutanix environment. The administrator wants to leverage Prism Central to create a policy that will block all traffic regardless of direction, between two groups of VMs identified by their category. Which policy should be used to meet this requirement?

- A. An Application Security Policy
- B. A Quarantine Policy
- C. A Whitelist-Based Policy
- D. An Isolation Environment Policy

Correct Answer: D



QUESTION 4

Which feature must be enabled in order to ensure that VMs are restarted on other hosts in the event of a host failure?

- A. High Availability
- B. VM Snapshots
- C. Network Segmentation
- D. Live Migration

Correct Answer: A

QUESTION 5

An administrator is commissioning a Nutanix Enterprise Cloud. Once the user VMs have been deployed and are running, the administrator finds that VMs on the same host are able to communicate, but are unable to communicate between hosts.

What must be changed to enable full inter-VM communications?

- A. Change the spanning-tree port type on the switch.
- B. Change the network the VMs are connected to
- C. Update the switch to specifically allow VLAN 15
- D. The VMs need to have static IP addresses.

Correct Answer: C

NCP-MCI-5.20 PDF Dumps

NCP-MCI-5.20 Exam Questions

NCP-MCI-5.20 Braindumps