

# NCP-MCI-6.5<sup>Q&As</sup>

Nutanix Certified Professional - Multicloud Infrastructure (NCP-MCI) v6.5 exam

# Pass Nutanix NCP-MCI-6.5 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.passapply.com/ncp-mci-6-5.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Nutanix Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





#### **QUESTION 1**

How many Prism Central instances are required to deploy Leap?

- A. One per availability zone
- B. One per customer environment
- C. One per physical site
- D. One per AHV cluster

Correct Answer: A

#### **QUESTION 2**

Refer to the exhibit.



Which two initial cluster configuration tasks were missed during the deployment process? (Choose two.)

- A. Host password changes
- B. Password policy changes
- C. BIOS password changes
- D. CVM password changes

Correct Answer: AD

#### **QUESTION 3**



### https://www.passapply.com/ncp-mci-6-5.html

2024 Latest passapply NCP-MCI-6.5 PDF and VCE dumps Download

An administrator is performing validation testing of a new-deploy cluster. During this test, the administrator disconnect each LAN interface from each of the nodes while pinging the hypervisor and guest VMs.

When the first interface is disconnected, pings continue as expected to the hypervisor, but pings stop responding from the guest. Pings continue when the interface is reconnected. When the second interface is disconnected, pings continue to both the hypervisor and guest VMs.

What could be the cause of this error?

- A. This is normal behavior for a LAN Failover
- B. Switch ports are configured with different VLANs
- C. Portfast is not enabled on the switch ports
- D. One of the network interfaces has a bad patch cable.

Correct Answer: B

Explanation: switch ports are configured with different VLANs could be the cause of this error. If the switch ports are not configured with the same VLANs as the network interfaces on each node, then there could be a mismatch in network connectivity when one interface is disconnected1. This could affect the guest VMs that are using a different VLAN than the hypervisor.

#### **QUESTION 4**

What is most likely the cause of this issue?

- A. There is a firewall rule blocking VLAN512 traffic
- B. VLAN512 is a reserved VLAN ID, and not usable for guest VMs.
- C. The VLAN was not created on the upstream switches.
- D. The administrator did not created the VLAN on all hosts

Correct Answer: C

#### **QUESTION 5**

An administrator is concerned about the amount of data that a VM reading and writing to the storage fabric. Which metric will provide that data?

- A. Host Hypervisor IO Bandwidth
- B. Host Disk IOPS
- C. VM Storage Controller IOPS
- D. VM Storage Controller Bandwidth

Correct Answer: C

## https://www.passapply.com/ncp-mci-6-5.html 2024 Latest passapply NCP-MCI-6.5 PDF and VCE dumps Download

<u>Latest NCP-MCI-6.5 Dumps</u> <u>NCP-MCI-6.5 VCE Dumps</u> <u>NCP-MCI-6.5 Practice Test</u>