



NS0-159^{Q&As}

NetApp Certified Data Administrator, ONTAP

Pass NetApp NS0-159 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-159.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You have a 4-node cluster and want to ensure that a new NAS LIF can fail over to any node. In this scenario, which two actions are required to configure the LIF? (Choose two.)

- A. Add ports from all nodes to the LIF's broadcast domain.
- B. Configure the failover policy to broadcast-domain-wide.
- C. Add ports from all nodes to the LIF's home port list.
- D. Configure the failover policy to system-defined.

Correct Answer: AD

QUESTION 2

You are running out of space on an aggregate and decide to move a FlexVol volume to a different aggregate. You do not want to move the Snapshot copies with the volume.

Which two actions satisfy your requirement? (Choose two.)

- A. Use the volume move command on the FlexClone volume.
- B. Use the storage aggregate relocation command on the node.
- C. Create a FlexClone volume.
- D. Use the volume rehost command on the FlexClone volume.

Correct Answer: AB

QUESTION 3

A customer wants to add nodes to an 8-node AFF A700 NAS cluster.

In this scenario, what is the maximum number of additional nodes?

- A. 12
- B. 24
- C. 8
- D. 16

Correct Answer: B

QUESTION 4



Which two statements about replicating FlexGroup volumes are true? (Choose two.)

- A. You can increase the capacity of a FlexGroup volume that is being replicated.
- B. You cannot perform a resync on a FlexGroup SnapMirror relationship after it has been broken.
- C. The SnapMirror relationship type must be XDP.
- D. The SnapMirror relationship type must be DP.

Correct Answer: AB

QUESTION 5

You need to create a new LIF on WLAN 10. The port-channel configuration on the upstream switch has VLAN 10 set to the native (untagged) VLAN.

In this scenario, what should be set as the LIF's home port?

- A. a0a
- B. a0a-10
- C. e0c-10
- D. e0c

Correct Answer: B

[NS0-159 PDF Dumps](#)

[NS0-159 Study Guide](#)

[NS0-159 Exam Questions](#)