



# NS0-162<sup>Q&As</sup>

NetApp Certified Data Administrator (ONTAP)

## Pass NetApp NS0-162 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-162.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

After deploying an ONTAP 9.8 cluster, you want to disable the unused Ethernet ports. In this scenario, which two methods would accomplish this task? (Choose two.)

- A. Use ONTAP System Manager.
- B. Use the command line interface.
- C. Use Active IQ Config Advisor.
- D. Use Active IQ Unified Manager.

Correct Answer: AB

---

### QUESTION 2

A company has three servers that are using the iSCSI protocol to connect to a 2 node NetApp ONTAP cluster. The server administrator notices that half of the paths are down. When you check the ONTAP cluster, you notice that the servers are toggling into only the first controller.

Which two steps do you take to troubleshoot the issue? (Choose two.)

- A. Verify that the UFs are up.
- B. Verify that the iSCSI data protocol has been enabled on the ports.
- C. Verify that each server has been rebooted.
- D. Verify that the controller has not been taken over.

Correct Answer: AB

---

### QUESTION 3

You have commissioned a new AFF A250 MetroCluster over IP configuration. Your company requires an automatic switchover to the surviving site in case of a site disaster. What do you need to configure to fulfill this requirement?

- A. cluster failover
- B. ONTAP Mediator service
- C. storage failover
- D. automated unplanned switchover

Correct Answer: B

Reference: [https://docs.netapp.com/us-en/ontap-metrocluster/pdfs/sidebar/Install\\_a\\_MetroCluster\\_IP\\_configuration.pdf](https://docs.netapp.com/us-en/ontap-metrocluster/pdfs/sidebar/Install_a_MetroCluster_IP_configuration.pdf)



(3)

Starting with ONTAP 9.7, the ONTAP Mediator service can assist the MetroCluster IP configuration in performing an automatic unplanned switchover by providing a physically separate repository for status information.

---

#### QUESTION 4

What establishes a quorum in a 4-node cluster?

- A. epsilon
- B. cluster peer
- C. ONTAP Mediator
- D. TieBreaker

Correct Answer: A

Reference: <https://library.netapp.com/ecmdocs/ECMP1196798/html/GUID-EFE1DEF4-8B87-4C4A-8E4E-C6C79F760710.html>

---

#### QUESTION 5

Which two storage efficiencies are enabled by default on NetApp AFF systems? (Choose two.)

- A. postprocess compaction
- B. Inline compression
- C. Inline deduplication
- D. postprocess zero block detection

Correct Answer: BC

[Latest NS0-162 Dumps](#)

[NS0-162 PDF Dumps](#)

[NS0-162 Study Guide](#)