



# NS0-173<sup>Q&As</sup>

Cisco and NetApp FlexPod Design Specialist

## Pass NetApp NS0-173 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-173.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

A customer with a FlexPod Express solution wants to enable remote access to the NetApp storage component.

In this scenario, which two access methods are recommended? (Choose two.)

- A. SAML
- B. SSH
- C. RDP
- D. Telnet

Correct Answer: BD

---

### QUESTION 2

You are designing a FlexPod solution with a 2-node storage system, multiple compute chassis, and ACI.

In this scenario, which two network switches are required? (Choose two.)

- A. leaf switch
- B. core switch
- C. cluster interconnect switch
- D. spine switch

Correct Answer: AD

Reference: <https://www.cisco.com/c/en/us/solutions/collateral/data-center-virtualization/application-centricinfrastructure/white-paper-c11-737909.html>

---

### QUESTION 3

What are characteristics of the Cisco UCS 5108 blade chassis?

- A. 4 RU, 6 half-width UCS B-Series blades, 160 Gbps I/O bandwidth
- B. 6 RU, 8 half-width UCS B-series blades, 160 Gbps I/O bandwidth
- C. 6 RU, 6 half-width UCS B-series blades, 80 Gbps I/O bandwidth
- D. 4 RU, 8 half-width UCS B-series blades, 40 Gbps I/O bandwidth

Correct Answer: B

Reference: [https://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-b-seriesblade-servers/spec\\_sheet\\_c17-644224.pdf](https://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-b-seriesblade-servers/spec_sheet_c17-644224.pdf)

---



#### QUESTION 4

A customer wants to deploy a FlexPod solution that involves directly connecting the NetApp AFF storage using the FCoE protocol to the Cisco UCS Fabric Interconnects.

In this scenario, which Cisco UCS Fibre Channel mode would be used to accomplish this task?

- A. trunk mode
- B. end host mode
- C. switching mode
- D. access mode

Correct Answer: C

Reference: <https://www.netapp.com/media/16411-nva-0025-deploy.pdf>

---

#### QUESTION 5

A customer is configuring the UCS to handle a multitenant environment. The customer has created an organization within UCS for each tenant and would like to allow access to these organizations for only users that belong to that tenant.

In this scenario, which feature in UCS Manager should the customer use to accomplish this task?

- A. Locales
- B. Trusted Platform Module
- C. Service Profile
- D. User Roles

Correct Answer: C

Reference: [https://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ucs-manager/GUI-User-Guides/Admin-Management/3-2/b\\_Cisco\\_UCS\\_Admin\\_Mgmt\\_Guide\\_3\\_2/b\\_Cisco\\_UCS\\_Admin\\_Mgmt\\_Guide\\_3\\_2\\_chapter\\_01010.html](https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Admin-Management/3-2/b_Cisco_UCS_Admin_Mgmt_Guide_3_2/b_Cisco_UCS_Admin_Mgmt_Guide_3_2_chapter_01010.html)

[NS0-173 VCE Dumps](#)

[NS0-173 Study Guide](#)

[NS0-173 Exam Questions](#)