



NS0-173^{Q&As}

Cisco and NetApp FlexPod Design Specialist

Pass NetApp NS0-173 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-173.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer with a FlexPod Express solution wants to enable remote access to the NetApp storage component.

In this scenario, which two access methods are recommended? (Choose two.)

- A. SAML
- B. SSH
- C. RDP
- D. Telnet

Correct Answer: BD

QUESTION 2

A customer is planning to deploy a FlexPod solution for a large scale SAN requirement that uses the FC protocol. The customer plans to use Smart Zoning in the configurations to reduce the number of TCAM entries in the zoning process.

In this scenario, which design would enable the customer to use Smart Zoning?

- A. storage connected to Cisco Nexus 9000 Series switches
- B. storage connected to Cisco Nexus 5000 Series switches
- C. storage connected to Cisco MDS switches
- D. storage directly connected to Cisco UCS Fabric Interconnects

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/UCS_CVDs/flexpod_datacenter_vmware_netappaffa_design.html#_Toc23952741

QUESTION 3

A client has a FlexPod Datacenter solution with four active fabric links in port channel mode established between the Cisco Fabric Interconnects and the IOMs on a Cisco 5108 blade chassis. The blade chassis is fully populated with Cisco UCS B200M5 blades. A worker in the data center inadvertently unplugs the fourth uplink cable from IOM-A while working in the rack.

In this scenario, what happens to the network traffic?

- A. Connectivity for servers 3, 4, 7, and 8 all fail over to IOM-B.
- B. There is a loss of connectivity for servers 4 and 8.
- C. Traffic is load-balanced within IOM-A.



D. Traffic is load-balanced within IOM-B.

Correct Answer: A

QUESTION 4

After you install a FlexPod infrastructure at a customer site, you need to migrate the existing VMware virtual machines off the infrastructure that was used before FlexPod was installed.

Which VMware vSphere feature accomplishes this task?

- A. vMotion
- B. vSphere DRS
- C. VM Component Protection
- D. vSphere HA

Correct Answer: A

QUESTION 5

A customer has verified physical connectivity on the FlexPod. However, the LUNs are not available on the Cisco UCS server. To make the LUNs visible to the UCS, the customer must enable a switching feature for zoning.

In this scenario, what should the customer do?

- A. Enable NPIV on all switches.
- B. Enable Spine mode on all the Cisco Nexus 9000 switches.
- C. Enable NPV on all switches.
- D. Enable the device connector feature in Cisco UCS Manager.

Correct Answer: D

[NS0-173 PDF Dumps](#)

[NS0-173 VCE Dumps](#)

[NS0-173 Brindumps](#)