



# NS0-175<sup>Q&As</sup>

Cisco and NetApp FlexPod Design Specialist

## Pass NetApp NS0-175 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-175.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

You are designing a FlexPod solution that requires 100GbE connectivity between all components.

In this scenario, what are two NetApp Controller types that would satisfy the requirement? (Choose two.)

- A. NetApp AFF A220
- B. NetApp AFF C190
- C. NetApp AFF A800
- D. NetApp AFF A400

Correct Answer: AD

---

### QUESTION 2

A customer has reviewed the latest vSphere CVD and asks you if they can use their older Cisco servers in the new FlexPod solution and still have supported configuration.

Which statement is true in this scenario?

- A. FlexPod configurations are fully supported if they follow the technical specifications and compatibility matrices.
- B. FlexPod configurations are fully supported if they follow a specific Cisco Validated Design.
- C. FlexPod configurations are fully supported regardless of the equipment used.
- D. FlexPod configurations are fully supported if they follow a specific NetApp Verified Architecture.

Correct Answer: B

Reference: <https://www.cisco.com/c/dam/en/us/solutions/collateral/data-center-virtualization/flexpod/flexpod-solution-overview.pdf>

---

### QUESTION 3

An administrator is designing a FlexPod solution with NetApp ONTAP 9.7 software with a logical separation of data for each department.

In this scenario, which two components must be part of the design? (Choose two.)

- A. IPspaces
- B. volumes
- C. virtual port channels



D. Storage Virtual Machines

Correct Answer: AB

---

#### QUESTION 4

A customer wants to refresh their FlexPod solution by moving from 10 Gbps to 40 Gbps networking. They use FCoE to boot from SAN.

In this scenario, which statement is true?

- A. FCoE is supported for 32 Gbps adapters
- B. FCoE is supported for 25 Gbps adapters
- C. FCoE is supported for 40 Gbps adapters
- D. FCoE is supported on only 10 Gbps unified adapters

Correct Answer: C

---

#### QUESTION 5

Which two support account levels are minimally required when you deploy a FlexPod Datacenter solution? (Choose two.)

- A. NetApp SupportEdge Expert NBD
- B. Cisco SmartNet Total Care 24x7x4
- C. NetApp SupportEdge Advisor 24x7x4
- D. Cisco Solution Support 24x7x4

Correct Answer: CD

---

[NS0-175 PDF Dumps](#)

[NS0-175 Study Guide](#)

[NS0-175 Braindumps](#)