



NS0-175^{Q&As}

Cisco and NetApp FlexPod Design Specialist

Pass NetApp NS0-175 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-175.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer deployed a FlexPod Datacenter solution six months ago that included Cisco UCS 6332 Fabric Interconnects with the default port license enabled. They will be performing an upgrade to the system which requires a reboot of the Fabric Interconnects (FI) and they want to ensure that the servers are available after the reboot.

In this scenario, how many ports on the FI will be active after the reboot?

- A. 16 ports
- B. 4 ports
- C. 8 ports
- D. 32 ports

Correct Answer: A

QUESTION 2

A customer wants to refresh their FlexPod solution by moving from 10 Gbps to 40 Gbps networking. They use FCoE to boot from SAN.

In this scenario, which statement is true?

- A. FCoE is supported for 32 Gbps adapters
- B. FCoE is supported for 25 Gbps adapters
- C. FCoE is supported for 40 Gbps adapters
- D. FCoE is supported on only 10 Gbps unified adapters

Correct Answer: C

QUESTION 3

A customer is unhappy with their current data center infrastructure. They want to purchase a FlexPod system to replace it. The customer asks you to help them understand the benefits of Solution Support to determine which support model would suit them best.

In this scenario, which three statements are correct? (Choose three.)

- A. You have a single point of contact for all cases
- B. Solution Support is a lower-cost support option



- C. There is no need to diagnose the problem before you call support
- D. Customers do not need to open tickets; all issues are automatically reported
- E. Issues are solved by solution experts

Correct Answer: ABE

QUESTION 4

A customer wants a low latency and high IOPS FlexPod solution and decides on an end-to-end NVMe design.

In this scenario, which three components are required to accomplish this task? (Choose three.)

- A. NetApp FAS with a 32Gbps FC HBA
- B. Cisco Application Policy Infrastructure Controller (APIC)
- C. Cisco MDS Series switches
- D. NetApp AFF with a 32Gbps FC HBA
- E. Cisco UCS Virtual Interface Card (VIC) 1400 series

Correct Answer: CDE

QUESTION 5

You want to ensure the uniqueness of the Cisco UCS WWNNs and WWPNS in the SAN for a FlexPod solution.

In this situation, Cisco recommends using which WWN prefix for all blocks in a pool?

- A. 30:00:00:25:B5:XX:XX:XX
- B. 40:00:00:25:B5:XX:XX:XX
- C. 20:00:00:25:B5:XX:XX:XX
- D. 60:00:00:25:B5:XX:XX:XX

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Storage-Mgmt/4-0/b_UCSM_GUI_Storage_Management_Guide_4_0/b_UCSM_GUI_Storage_Management_Guide_4_0_chapter_0111.html