



NS0-182^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-182 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-182.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer wants to reduce the disk allocation requirement for the root aggregate and increase usable storage by partitioning the disks into one large part and one small part. The small part is used for the root aggregate and the large part for the data aggregates.

In this situation, what is this feature called?

- A. ONTAP
- B. storage virtual machine
- C. Advanced Drive Partitioning
- D. RAID

Correct Answer: C

QUESTION 2

Without adding new cluster interconnect switches, you want to nondisruptively upgrade from FAS2554 controllers to FAS8200 controllers on an existing 2-node switchless cluster running ONTAP 9.5 software.

Which statement is correct in this scenario?

- A. Relocate the aggregates to one FAS2554 node, takeover, replace the node in takeover state with a FAS8200 node, reassign the disks, giveback, and repeat for the second node.
- B. Connect the FAS8200 to the FAS2554 with interconnect cables, join the existing cluster, relocate the aggregates from the FAS2554 to the FAS8200, and decommission the FAS2554.
- C. Set up the FAS8200 as a new cluster, move the SVMs from the FAS2554 to the FAS8200 using SVM move, and decommission the FAS2554.
- D. You cannot perform this task nondisruptively.

Correct Answer: A

QUESTION 3

You are adding two new nodes into an existing switchless 2-node cluster.

Which two statements are true in this scenario? (Choose two.)

- A. You first need to install the cluster interconnect switches to the existing cluster.
- B. You must make sure that the existing nodes are healthy and that all cluster links are up.
- C. The existing cluster must use clustered Data ONTAP 8.1 or later software.
- D. You need to schedule downtime to add these two nodes.



Correct Answer: AB

QUESTION 4

You were asked to install a FAS9000 with two quad-port SAS PCI cards. The SAS PCI cards are installed in slot 9 and slot 1. In preparation for the installation, you are filling out the SAS cabling worksheet.

In this scenario, which ports are used for the second stack?

- A. 9a/1d
- B. 9c/1a
- C. 9b/1b
- D. 9a/1a

Correct Answer: C

QUESTION 5

You are configuring a new system with ONTAP 9.5. You created interface groups, VLANs, and a broadcast domain for the new ports on all the nodes of your cluster. During the configuration, you used an MTU value of 1500 for the broadcast domain and 9000 for the physical ports. The customer asks you to enable jumbo frames.

What should you do in this scenario?

- A. Set the MTU option to jumbo frames on the broadcast domain.
- B. Change the MTU value to 9000 on the ifgroup.
- C. Set the MTU option to jumbo frames on the ifgroup.
- D. Change the MTU value to 9000 on the broadcast domain.

Correct Answer: D

[Latest NS0-182 Dumps](#)

[NS0-182 Study Guide](#)

[NS0-182 Braindumps](#)