NS0-183^Q&As

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-183 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/ns0-183.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

You are installing a new AFF A400 cluster that is running ONTAP 9.7 software. You are asked to attach an Amazon S3 cloud tier for FabricPool technology.

In this scenario, which two NetApp License File (NLF) types are supported for cloud tiering? (Choose two.)

A. term-based

B. perpetual

C. base

D. master

Correct Answer: AB

Reference: https://www.netapp.com/pdf.html?item=/media/17239-tr4598pdf.pdf (10)

QUESTION 2

Which two SVMs are automatically created during the cluster setup? (Choose two.)

A. admin SVM

B. system SVM

C. node SVM

D. data SVM

Correct Answer: AB

QUESTION 3

You are setting up a new AFF A400 that will serve iSCSI LUNs. You will have four iSCSI SVMs that each need to connect to an Internet Storage Name Service (iSNS) for discovery and management purposes.

In this scenario, which network interface is needed for each SVM to register with the name service?

A. SVM data LIF

B. SVM management LIF

C. node management LIF

D. intercluster LIF

Correct Answer: D

QUESTION 4

Click the Exhibit button.

```
cluster1::> network device-discovery show

Node/          Local  Discovered
Protocol       Port   Device                              Interface           Platform
------------   -----  -------------------------------     ----------------    -----------------
node1/cdp
               e4a    switchA-NX.netapp.com(SSI142311PD)
                                                          e1/1/1-4            N3K-C3132Q-V
               e8a    switchA-NX.netapp.com(SSI142311PD)
                                                          e1/2/1-4            N3K-C3132Q-V
node2/cdp
               e4a    switchB-NX.netapp.com(SSI142311PE)
                                                          e1/1/1-4            N3K-C3132Q-V
               e8a    switchB-NX.netapp.com(SSI142311PE)
                                                          e1/2/1-4            N3K-C3132Q-V
```

You are reviewing the setup of a recently installed FAS9000 switched cluster. As shown in the exhibit, the cluster interconnects are connected to a pair of Cisco Nexus 3132Q-V 40 Gb ports.

For a high availability, which ports should swap Ethernet cables?

A. Swap node1:e8a and node2:e4a.

B. Swap node1:e4a and node1:e8a.

C. Swap node2:e4a and node2:e8a.

D. Swap node1:e4a and node2:e4b.

Correct Answer: C

QUESTION 5

You are asked to add a new HA pair to an existing 2-node switchless AFF A220 cluster. You must first convert to a 2-node switched cluster using Broadcom BES-53248 cluster switches.

Which two conditions must be fulfilled before you start the migration? (Choose two.)

A. All cluster LIFs must be in the up state and on their home ports.

B. The "Enabled Switchless Cluster" option must be manually set to "false".

C. All cluster LIFs must have an MTU size of 1500.

D. The 2-node switchless configuration must be properly set up and functioning.

Correct Answer: AD

Reference: https://docs.netapp.com/platstor/index.jsp?topic=%2Fcom.netapp.doc.hw-sw-ix8-migrate-2n%2FGUID-81FD5EDF-8902-40EA-9050-69358426CB6F.html