

NS0-184^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-184 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/ns0-184.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by NetApp Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which two SVMs are automatically created during the cluster setup? (Choose two.)

- A. admin SVM
- B. system SVM
- C. node SVM
- D. data SVM

Correct Answer: AB

QUESTION 2

You completed an ONTAP cluster deployment as a reseller engineer. During the knowledge transfer process to the customer, they ask for proof that the array has correct multi-path HA cabling deployed and that the array is error free.

Which documentation output would you present to the customer to satisfy this requirement?

- A. Active IQ Unified Manager output
- B. NetAppDocs output
- C. Config Advisor output
- D. Active IQ OneCollect output

Correct Answer: C

Reference: https://docs.netapp.com/platstor/topic/com.netapp.doc.hw-controller-add/GUID-64A513391F03-451C-B062-9F97E772817E.html

QUESTION 3

You have installed a new 2-node FAS9000 cluster with two external shelves. You want to make sure that each node has two paths to each disk in the shelves.

How do you verify your configuration?

- A. Use the storage show disk -p command.
- B. Use the storage disk option show command.
- C. Use the disk show -fields initiator command.
- D. Use the sysconfig command.

Correct Answer: C



QUESTION 4

In an ONTAP 9.7 cluster, which LIF role is used for sending AutoSupport, establishing Network Time Protocol (NTP), and loading software updates?

- A. cluster management LIF
- B. node management LIF
- C. data LIF
- D. cluster LIF

Correct Answer: B

Reference: https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-nmg%2FGUIDDFFBE8D9-E824-4085-8FA2-24E367288CB8.html

QUESTION 5

Click the Exhibit button.

Welcome to node setup.

You can enter the following commands at any time: "help" or "?" - if you want to have a question clarified, "back" - if you want to change previously answered questions, and "exit" or "quit" - if you want to quit the setup wizard. Any changes you made before quitting will be saved.

To accept a default or cmit a question, do not enter a value.

Enter the node management interface port [e0c]:

You want to add a FAS2750 HA pair to an existing 6-node cluster.

Referring to the exhibit, which action would you perform to begin adding the node?

- A. Use the back command to begin the Cluster Setup wizard.
- B. Reboot the node and enter maintenance mode and run the Cluster Setup wizard.
- C. Use the node setup wizard and select 0a as the management interface.
- D. Use the exit or quit commands then run the cluster setup command.

Correct Answer: C

Reference: http://docs.netapp.com/ontap-9/topic/com.netapp.doc.dot-cm-sag/System% 20administration.pdf (35)



Latest NS0-184 Dumps

NS0-184 Practice Test

NS0-184 Study Guide