NS0-193$^{Q\&As}$

NetApp Certified Support Engineer

Pass NetApp NS0-193 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/ns0-193.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

You deploy an AFF storage system that is running ONTAP 9.5.

In this scenario, which three features are enabled by default? (Choose three.)

A. inline adaptive compression

B. inline secondary compression

C. postprocess compression

D. aggregate-level deduplication

E. inline data compaction

Correct Answer: ABE

QUESTION 2

Which two statements are true about space-reserved LUNs? (Choose two.)

A. If the LUN\\\'s volume has a space guarantee of "none", then free space is allocated to the LUN at creation time.

B. If the LUN\\\'s volume has a space guarantee of "volume", then free space is allocated to the LUN at write time.

C. If the LUN\\\'s volume has a space guarantee of "volume", then free space is allocated to the LUN at creation time.

D. If the LUN\\\'s volume has a space guarantee of "none", then free space is allocated to the LUN at write time.

Correct Answer: AC

Reference: https://kb.netapp.com/app/answers/answer_view/a_id/1002502/~/faq%3A-how-is-spaceutilization-managed-in-a-data-ontap-san-environment%3F

QUESTION 3

Which sequence of actions should you perform after replacing a memory DIMM?

A. From the loader prompt, start diagnostics mode.

B. From the special boot menu, select option 6, Update flash, from the backup configuration.

C. From the special boot menu, select option 4, Clean configuration, and initialize all disks.

D. From the loader prompt, boot the backup image.

Correct Answer: A

Reference: https://library.netapp.com/ecm/ecm_download_file/ECMP1119134

QUESTION 4

You have a 4-node cluster. You want to ensure that a NAS data LIF can only migrate to ports that are on its home node, and its HA partner.

In this scenario, which failover policy would be configured?

A. sfo-partner-only

B. local-only

C. system-defined

D. broadcast-domain-wide

Correct Answer: C

Reference: https://www.google.com/url? sa=tandrct=jandq=andesrc=sandsource=webandcd=7andved=2ahUKEwigzre8 xY_nAhWYzzgGHVbFBg4QFjAGegQIBh ABandurl=ftp%3A%2F%2Fftp.aau.edu.et%2FTraining%2FAAU-Private-Cloud%2FData_ONTAP % 2FNetwork%2520Management%2520Guide.pdfandusg=AOvVaw0Zay5aRX7V7yB2kkmY7hAS

QUESTION 5

You have configured an ONTAP system. You want to verify that AutoSupport is being delivered to NetApp. In this scenario, what are two ways to accomplish this task? (Choose two.)

A. Review AutoSupport messages in Active IQ.

B. Review the AutoSupport section in OnCommand Unified Manager.

C. Review the AutoSupport section in OnCommand System Manager.

D. Use the system node autosupport history show command.

Correct Answer: AC