



NS0-505^{Q&As}

NetApp Certified Implementation Engineer – SAN ESeries

Pass NetApp NS0-505 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-505.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the `base` host connectivity provided by the E2600 controller? (Choose the best answer.)

- A. None
- B. IB
- C. iSCSI
- D. SAS
- E. FC

Correct Answer: D

QUESTION 2

When you arrive on a customer site, you discover that the customer network administrator has called in sick. While required power has been provided and all of the components ordered have been physically accounted for, the network will not be operational today.

Which would be the most useful tool to complete your rack and stack and initial configuration of the system?

(Choose the best answer.)

- A. a Serial Port cable
- B. a CD containing the 10.86 version of SANtricity
- C. a standalone switch or hub
- D. None of the above, come back tomorrow.

Correct Answer: B

QUESTION 3

Which interface launches the script engine for a storage system? (Choose the best answer.)

- A. MPIO
- B. DDP
- C. ALUA
- D. AMW
- E. EMW



Correct Answer: E

QUESTION 4

A customer has an E-Series system with several expansion enclosures and can use the _____ to determine if the connections between the enclosures have been cabled correctly. (Choose the best answer.)

- A. Recovery Guru
- B. Major Event Log
- C. Host Mappings tab
- D. Cable Connections report

Correct Answer: D

QUESTION 5

What is the first step when replacing a FRU component on a running storage system? (Choose the best answer.)

- A. Disconnect the cables from the management ports.
- B. Power down the array before changing the part.
- C. Remove the part and check SANtricity for continuing errors.
- D. Use SANtricity to view the target component and place the component off-line or in service mode before removing the part.

Correct Answer: D

[NS0-505 VCE Dumps](#)

[NS0-505 Study Guide](#)

[NS0-505 Braindumps](#)