



# NS0-509<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN - ONTAP

## Pass NetApp NS0-509 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-509.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

You want to ensure maximum performance of iSCSI LUNs on an AFF A220. In this scenario, which two actions will accomplish this task? (Choose two.)

- A. Disable flow control.
- B. Configure virtual LAN (VLAN).
- C. Enable flow control.
- D. Enable jumbo frames.

Correct Answer: CD

### QUESTION 2

Which two components must be verified for a supported NetApp SAN confutation? (Choose two.)

- A. host memory
- B. host GPU
- C. host multipath
- D. host bus adapter

Correct Answer: CD

### QUESTION 3

Click the Exhibit button.

Question		Exhibit				
c11::> network fcp adapter show						
Node	Adapter	Connection Established	Port Address	Admin Status	Operational Status	
node1	0e	false	0	up	link	not connected
node1	0f	false	0	up	link	not connected
node1	0g	false	0	up	link	not connected
node1	0h	false	0	up	link	not connected
node2	0e	false	0	up	link	not connected
node2	0f	false	0	up	link	not connected
node2	0g	false	0	up	link	not connected
node2	0h	false	0	up	link	not connected

You have an existing 2-node AFF A300 cluster with premium bundle licensing applied. You need to have consistently low front end latency, and have determined that NVMe satisfies this requirement.



Referring to the exhibit, which two actions would accomplish this task? (Choose two.)

- A. Add a UTA2 adapter to each of the two AFF A300 nodes.
- B. Add a 32 GB FC HBA to each of the two AFF A300 nodes.
- C. Apply the license for FCP.
- D. Apply the license for NVMe.

Correct Answer: BD

---

#### QUESTION 4

An enterprise customer has both a NetApp FAS8200 4-node cluster and a third-party storage array in a shared SAN environment. The host servers connect to both storage vendors' arrays in the fabric. Regarding the hosts in this scenario, what are two NetApp best practices when performing this task? (Choose two.)

- A. Set the default timeout values and storage parameters for the host system.
- B. Provide isolation between storage systems using NetApp's multitenancy feature.
- C. Always use the same adapter for heterogeneous storage systems.
- D. Use separate adapters to connect to each vendor's storage system.

Correct Answer: AD

---

#### QUESTION 5

You will be purchasing two high availability NetApp AFF A700s systems. You want to set up a 4-node cluster. Which switch would you use for the cluster interconnect switches?

- A. NetApp CN1610
- B. Cisco Nexus 3132Q-V
- C. Cisco Nexus 5548UP
- D. Cisco Nexus 5020

Correct Answer: B

[NS0-509 PDF Dumps](#)

[NS0-509 VCE Dumps](#)

[NS0-509 Braindumps](#)