

NS0-509^{Q&As}

NetApp Certified Implementation Engineer - SAN - ONTAP

Pass NetApp NS0-509 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.passapply.com/ns0-509.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.passapply.com/ns0-509.html 2024 Latest passapply NS0-509 PDF and VCE dumps Download

QUESTION 1

An administrator needs to determine the maximum volume size that is supported per operating system. Which resource has this information?

- A. Config Advisor
- B. OneCollect
- C. Interoperability Matrix Tool (IMT)
- D. Hardware Universe (HWU)

Correct Answer: C

QUESTION 2

On your ONTAP 9.5 cluster, you need to set up the onboard key manager with hardware-based security and volume encryption.

Which two licenses are required in this situation? (Choose two.)

- A. FDE
- B. TPM
- C. VE
- D. RSA

Correct Answer: CD

QUESTION 3

Exhibit.



https://www.passapply.com/ns0-509.html

2024 Latest passapply NS0-509 PDF and VCE dumps Download

Referring to the exhibit, which FC LIF would cause a path failure on a host connecting to a LUN?

- A. fcp_sanluns01prod02p0e
- B. fcp_sanluns01prod02p0g
- C. fcp_sanluns01prod02p0g
- D. fcp_sanluns0lptodOlp0e

Correct Answer: A

QUESTION 4

When planning out a new FC SAN implementation for a AFF cluster, which two variables should be considered for a highly-available, resilient solution? (Choose two.)

- A. Length of LC/LC optic cables
- B. Multiple disk shelves
- C. Multiple PDUs connected to separate circuits
- D. Data-fabric zones using multiple switches

Correct Answer: CD

QUESTION 5

Click the Exhibit button.

Question Exhibit C11-02::> network interface show -vserver SVM1						
c11-02::>	network inter	riace show -	-vserver SVM1			
	Logical	Status	Network	Current	Current	Is
Vserver	Interface	Admin/Oper	Address/Mask	Node	Port	Home
SVM1						
	LIF_bot-0e	up/up	20:17:00:a0:98:5a:5c:af	cl1-02	0e	true
	LIF_bot-0f	up/up	20:19:00:a0:98:5a:5c:af	cl1-02	Of	true
	LIF_top-0e	up/up	20:16:00:a0:98:5a:5c:af	cl1-01	0e	true
	LIF_top-0f	down/down	20:18:00:a0:98:5a:5c:af	cl1-01	Of	true

During pre-deployment testing, you want to ensure that all FC paths are available to your host. You use the network interface modify -vserver SVM1 -lif LIF_top-0f -admin-state up command to correct the configuration shown in the exhibit.

What happens when using this command?

- A. It creates a new LIF on SVM2 named up.
- B. It creates a new LIF on SVM1 named LIF_top-0f.



https://www.passapply.com/ns0-509.html

2024 Latest passapply NS0-509 PDF and VCE dumps Download

C. It changes the administrative state from "down" to "up".

D. It changes the operational state from "down" to "up".

Correct Answer: C

NS0-509 VCE Dumps

NS0-509 Practice Test

NS0-509 Study Guide