NS0-509^{Q&As}

NS0-509^{Q&As}

NetApp Certified Implementation Engineer - SAN - ONTAP

Pass NetApp NS0-509 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/ns0-509.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

QUESTION 1

You are provisioning a LUN using an ISCSI initiator on an ESX host. You disable Ethernet flow control for

all ports but are experiencing Performance issues.

In this scenario, which two actions would improve the performance issue? (Choose two.)

A. Set the MTU settings 1500 for optimal performance.

B. Dedicate your ports to ISCSI traffic.

C. Enable jumbo frames across the entire data path.

D. Confirm that your host .mil storage polls are connected to a different network.

Correct Answer: BC

QUESTION 2

You are planning to implement a 32 Gb FC SAN on a 2-node AFF A700 ONTAP 9.5 cluster. You need to create 112 FC LIFs across the HA pair with a limit of 20 FC LIFs per physical HBA port.

In this scenario, how many 2-port 32 Gb HBA cards do you need per storage controller?

B. 1

C. 4

D. 3

Correct Answer: A

QUESTION 3

Click the Exhibit button.

Question	Exhibit

```
::> volume show -vserver svm1 -fields space-guarantee
 vserver   volume space-guarantee
--------------------------------------------------------------------
 svm1      vol1    volume

::> tun show -fields space-reserve
 vserver path                           space-reserve
--------------------------------------------------------------------
 svm1      /vol/vol1/qtree1/lun1   disabled
```

Referring to the exhibit, which container gains space savings from deduplication, compression and compaction?

A. the aggregate

B. the qtree

C. the volume

D. the LUN

Correct Answer: C

QUESTION 4

After the addition of extra DS224C disk shelves, you notice that the output of the system node run -node node_1 sysconfig command shows Mixed-path. You need to investigate why the additional shelves are providing this error.

In this scenario, which two tools would help diagnose this issue? (Choose two.)

A. Config Advisor

B. Active IQ

C. Hardware Universe (HWU)

D. Interoperability Matrix Tool (IMT)

Correct Answer: AD

QUESTION 5

Click the Exhibit button.

Question | Exhibit

```
cl1::> ucadmin show
                           Current  Current  Pending  Pending  Admin
Node            Adapter    Mode     Type     Mode     Type     Status
----------------------------------------------------------------------
01a             0e         cna      target   -        -        online
01a             0f         cna      target   -        -        online
01a             0g         cna      target   -        fc       online
01a             0h         cna      target   -        fc       online
01b             0e         cna      target   -        -        online
01b             0f         cna      target   -        -        online
01b             0g         fc       target   -        -        online
01b             0h         fc       target   -        -        online
```

Referring to the exhibit, which two pairs of ports are currently configurable as FC SAN LIFs? (Choose two.)

A. 01b, 0h

B. 01a, 0g

C. 01a, 0h

D. 01b, 0g

Correct Answer: BC