



# NS0-520<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN ONTAP

## Pass NetApp NS0-520 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ns0-520.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

An administrator is planning a hardware refresh and data migration from a Data ONTAP 7.3 system to new AFF A3-00 cluster that is using ONTAP 9.0. The Mode system only serves FC LUNs to a Windows 2012Rs server cluster that needs to remain connected after migration Referring to the scenario, which method would be used for the LUN migration.

- A. Unified Host Utility Kit
- B. 7-Mode Transition Tool (7MIT)
- C. Foreign LUN import (FLI)
- D. Oncommand system Manager

Correct Answer: B

### QUESTION 2

Exhibit.

```
cl1::> lun mapping show
vservers      path                igroup lun-id reporting-nodes
-----
SVM1          /vol/host1/lun0     linux1 0      cl1-01, cl1-02
SVM1          /vol/host2/lun0     linux2 0      cl1-01, cl1-02

cl1::> lun show
vservers      path                State  Mapped  Type  Size
-----
SVM1          /vol/host1/lun0     online mapped  linux 10GB
SVM1          /vol/host2/lun0     online mapped  linux 20MB
```

During a data mobility test on a 4-node ONTAP 9.3 cluster, the host loses direct access to its LUNs. The LUNs are hosting on node cl1-01 and are being moved to cl1-03 on a different HA pair. Referring to the exhibit, which corrective step is needed to ensure access while the volume is moved?

- A. Add reporting nodes for cl1-03 and cl1-04.
- B. Create additional LIFs on cl1-01 and cl1-02.
- C. Create a new destination volume on cl1-03.
- D. Create new igroups on cl1-03 and cl1-04.

Correct Answer: A

### QUESTION 3

For which two purposes would the use of VLANs be beneficial? (Choose two.)



- A. to isolate iSCSI traffic from LAN/WAN traffic
- B. to separate LAN from WAN traffic
- C. to isolate management traffic from other IP traffic
- D. to isolate UDP from TCP traffic in the IP network
- E. to isolate SSH traffic from other IP traffic

Correct Answer: AC

#### QUESTION 4

Question

Exhibit

```
::> volume efficiency show -inst
```

```
Vserver Name: svm1
Volume Name: vol1
Volume Path: /vol/vol1
State: Enabled
Status: Idle
Progress: Idle for 06:12:36
Type: Regular
Schedule: -
Efficiency Policy Name: inline-only
. . .
Compression: true
Inline Compression: true
Constituent Volume: false
Inline Dedupe: true
Data Compaction: false
Cross Volume Inline Deduplication: false
Cross Volume Background Deduplication: false
```

```
::> df -s -vserver svm1 -volume vol1
Filesystem      used      total-saved    %total-saved    deduplicated    %
deduplicated    compressed    %compressed
/vol/vol1/      29524919032  14762459516    50%             14762459516    50%    0    0%
```

You are troubleshooting high CPU use on a FAS8200 with all SAS HDDs. You have SAN hosts with LUNs in a volume named vol1. You want to reduce CPU use and maintain storage efficiencies. Referring to the exhibit which three actions will accomplish this task? (Choose three.)

- A. Disable compression.
- B. Enable cross-volume deduplication.
- C. Disable inline deduplication.
- D. Enable post process deduplication.
- E. Enable data compaction.

Correct Answer: CDE

#### QUESTION 5



Question	Exhibit					
<pre>cluster01::&gt; system hardware unified-connect show -node cluster01-01</pre>						
Node	Adapter	Current Mode	Current Type	Pending Mode	Pending Type	Admin Status
cluster01-01	0c	can	target	-	-	online
cluster01-01	0d	can	target	-	-	online
cluster01-01	1a	fc	target	-	-	offline
cluster01-01	1b	fc	target	-	-	offline
cluster01-01	1c	fc	initiator	-	-	online
cluster01-01	1d	fc	initiator	-	-	online
6 entries were displayed.						

Referring to the exhibit, what happens when you change the type for port 1a from target to initiator?

- A. The port type for 1a changes to initiator, and you must reboot the controller for the changes to take effect.
- B. You receive an error message that you must take ports 1a and 1b offline before you can change the type.
- C. B. You receive an error message that you must take the port 1a offline before you can change the type.
- D. The port type for 1a and 1b changes to initiator, and you must reboot the controller for the changes to take effect.

Correct Answer: A

[NS0-520 VCE Dumps](#)

[NS0-520 Study Guide](#)

[NS0-520 Exam Questions](#)