



NSE4_FGT-6.0^{Q&As}

Fortinet NSE 4 - FortiOS 6.0

Pass Fortinet NSE4_FGT-6.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse4_fgt-6-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Examine the network diagram and the existing FGT1 routing table shown in the exhibit, and then answer the following question:



```

FGT1 # get router info routing-table all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
* - candidate default;

S    172.20.0.0/16 [10/0] via 172.21.1.2, port2
C    172.21.0.0/16 is directly connected, port2
C    172.11.11.0/24 is directly connected, port1
  
```

An administrator has added the following static route on FGT1.

New Static Route

Destination ⓘ	<div style="background-color: #4CAF50; color: white; padding: 2px; text-align: center; font-weight: bold;">Subnet</div> <input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value="172.20.1.0/24"/>	<div style="background-color: #4CAF50; color: white; padding: 2px; text-align: center; font-weight: bold;">Named Address</div> <input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value="172.11.12.1"/>	<div style="background-color: #4CAF50; color: white; padding: 2px; text-align: center; font-weight: bold;">Internet Service</div> <input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text"/>
Gateway	<input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value="172.11.12.1"/>		
Interface	<input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value="port1"/>		
Administrative Distance ⓘ	<input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value="10"/>		
Comments	<input style="width: 95%; border: none; border-bottom: 1px solid #ccc;" type="text" value=""/>		
Status	<div style="display: flex; justify-content: space-around; align-items: center;"> ➤ Enabled ➤ Disabled </div>		

Advanced Options

Priority ⓘ

Since the change, the new static route is not showing up in the routing table. Given the information provided, which of the following describes the cause of this problem?

- A. The new route's destination subnet overlaps an existing route.
- B. The new route's Distance value should be higher than 10.
- C. The Gateway IP address is not in the same subnet as port1.



D. The Priority is 0, which means that this route will remain inactive.

Correct Answer: C

QUESTION 2

Which is a requirement for creating an inter-VDOM link between two VDOMs?

- A. The inspection mode of at least one VDOM must be proxy-based.
- B. At least one of the VDOMs must operate in NAT mode.
- C. The inspection mode of both VDOMs must match.
- D. Both VDOMs must operate in NAT mode.

Correct Answer: B

QUESTION 3

Which of the following statements about backing up logs from the CLI and downloading logs from the GUI are true? (Choose two.)

- A. Log downloads from the GUI are limited to the current filter view
- B. Log backups from the CLI cannot be restored to another FortiGate.
- C. Log backups from the CLI can be configured to upload to FTP as a scheduled time
- D. Log downloads from the GUI are stored as LZ4 compressed files.

Correct Answer: BC

QUESTION 4

View the exhibit:

Status	Name	VLAN ID	Type	IP/Netmask
Physical(12)				
🟢	port1		Physical Interface	10.200.1.1 255.255.255.0
	port1-VLAN1	1	VLAN	10.200.5.1 255.255.255.0
	port1-VLAN10	10	VLAN	10.0.10.1 255.255.255.0
🟢	port2		Physical Interface	10.200.2.1 255.255.255.0
	port2-VLAN1	1	VLAN	10.0.5.1 255.255.255.0
	port2-VLAN10	10	VLAN	10.0.20.254 255.255.255.0
🟢	port3		Physical Interface	10.0.1.254 255.255.255.0



Which statement about the exhibit is true? (Choose two.)

- A. Broadcast traffic received in port1-VLAN10 will not be forwarded to port2-VLAN10.
- B. port-VLAN1 is the native VLAN for the port1 physical interface.
- C. port1-VLAN10 and port2-VLAN10 can be assigned to different VDOMs.
- D. Traffic between port1-VLAN1 and port2-VLAN1 is allowed by default.

Correct Answer: AC

QUESTION 5

Which statement about DLP on FortiGate is true?

- A. It can archive files and messages.
- B. It can be applied to a firewall policy in a flow-based VDOM
- C. Traffic shaping can be applied to DLP sensors.
- D. Files can be sent to FortiSandbox for detecting DLP threats.

Correct Answer: A

[NSE4_FGT-6.0 PDF Dumps](#) [NSE4_FGT-6.0 VCE Dumps](#) [NSE4_FGT-6.0 Braindumps](#)