



NSE7_EFW-6.0^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.0

Pass Fortinet NSE7_EFW-6.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_efw-6-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

View the following FortiGate configuration.

```
config system global
    set snat-route-change disable
end
config router static
    edit 1
        set gateway 10.200.1.254
        set priority 5
        set device "port1"
    next
    edit2
        set gateway 10.200.2.254
        set priority 10
        set device "port2"
    next
end
```

All traffic to the Internet currently egresses from port1. The exhibit shows partial session information for Internet traffic from a user on the internal network.

```
FGT # diagnose sys session list
session info: proto=6 proto_state=01 duration=600 expire=3179 timeout=3600 flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=4
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=log may_dirty npu f00
statistic(bytes/packets/allow_err): org=3208/25/1 reply=11144/29/1 tuples=2
tx speed(Bps/kbps): 0/0 rx speed(Bps/kbps): 0/0
origin->sink: org pre->post, reply pre->post dev=4->2/2->4 gwy=10.200.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:64907->54.239.158.170:80(10.200.1.1:64907)
hook=pre dir=reply act=dnat 54.239.158.170:80->10.200.1.1:64907(10.0.1.10:64907)
pos/(before,after) 0/(0,0), 0/(0,0)
src_mac=b4:f7:a1:e9:91:97
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00317c5b tos=ff/ff app_list=0 app=0 url_cat=0
rpd_b_link_id = 00000000
dd_type=0 dd_mode=0
npu_state=0x000c00
npu info: flag=0x00/0x00, offload=0/0, ips_offload=0/0, epid=0/0, ipid=0/0, vlan=0x0000/0x0000
vlifid=0/0, vtag_in=0x0000/0x0000 in_npu=0/0, out_npu=0/0, fwd_en=0/0, qid=0/0
no_ofld_reason:
```

If the priority on route ID 1 were changed from 5 to 20, what would happen to traffic matching that user's session?

A. The session would be deleted, so the client would need to start a new session.



- B. The session would remain in the session table, and its traffic would still egress from port1.
- C. The session would remain in the session table, and its traffic would start to egress from port2.
- D. The session would remain in the session table, but its traffic would now egress from both port1 and port2.

Correct Answer: B

QUESTION 2

Which of the following statements about bulk configuration changes using FortiManager CLI scripts are correct? (Choose two.)

- A. When executed on the All FortiGate in ADOM, changes are automatically installed without creating a new revision history.
- B. When executed on the Remote FortiGate directly, administrators do not have the option to review the changes prior to installation.
- C. When executed on the Device Database, you must use the installation wizard to apply the changes to the managed FortiGate.
- D. When executed on the Policy Package, ADOM database, changes are applied directly to the managed FortiGate.

Correct Answer: BC

QUESTION 3

What conditions are required for two FortiGate devices to form an OSPF adjacency? (Choose three.)

- A. OSPF IP MTUs match.
- B. OSPF costs match.
- C. OSPF peer IDs match.
- D. IP addresses are in the same subnet.
- E. Hello and dead intervals match.

Correct Answer: ADE

QUESTION 4

Which of the following statements are correct regarding application layer test commands? (Choose two.)

- A. Some of them display statistics and configuration information about a feature or process.
- B. They are used to filter real-time debugs.
- C. They display real-time application debugs.



D. Some of them can be used to restart an application.

Correct Answer: AD

QUESTION 5

View these partial outputs from two routing debug commands:

```
# get router info kernel
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.1.254
dev=2(port1)
tab=254 vf=0 scope=0 type=1 proto=11 prio=10 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.2.254
dev=3(port2)
tab=254 vf=0 scope=253 type=1 proto=2 prio=0 0.0.0.0/0.0.0.0/0->10.0.1.0/24 pref=10.0.1.254 gwy=0.0.0.0
dev=4(port3)
# get router info routing-table all
S*      0.0.0.0/0 [10/0] via 10.200.1.254, port1
        [10/0] via 10.200.2.254, port2, [10/0]
C       10.0.1.0/24 is directly connected, port3
C       10.200.1.0/24 is directly connected, port1
C       10.200.2.0/24 is directly connected, port2
```

Which outbound interface will FortiGate use to route web traffic from internal users to the Internet?

A. Both port1 and port2

B. port3

C. port2

D. port1

Correct Answer: A

[NSE7_EFW-6.0 VCE
Dumps](#)

[NSE7_EFW-6.0 Practice
Test](#)

[NSE7_EFW-6.0
Braindumps](#)