



NSE7_EFW-6.2^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.2

Pass Fortinet NSE7_EFW-6.2 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_efw-6-2.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which configuration can be used to reduce the number of BGP sessions in an IBGP network?

- A. Neighbor range
- B. Route reflector
- C. Next-hop-self
- D. Neighbor group

Correct Answer: B

Route reflectors help to reduce the number of IBGP sessions inside an AS. A route reflector forwards the routes learned from one peer to the other peers. If you configure route reflectors, you don't need to create a full mesh IBGP network. All clients in a cluster only talk to route reflector to get sync routing updates. Route reflectors pass the routing updates to other route reflectors and border routers within the AS.

QUESTION 2

Examine the output of the `diagnose ips anomaly list` command shown in the exhibit; then answer the question below.

```
# diagnose ips anomaly list
```

```
list nids meter:
```

```
id=ip_dst_session      ip=192.168.1.10    dos_id=2  exp=3646  pps=0  freq=0
id=udp_dst_session     ip=192.168.1.10    dos_id=2  exp=3646  pps=0  freq=0
id=udp_scan            ip=192.168.1.110   dos_id=1  exp=649   pps=0  freq=0
id=udp_flood           ip=192.168.1.110   dos_id=2  exp=653   pps=0  freq=0
id=tcp_src_session     ip=192.168.1.110   dos_id=1  exp=5175  pps=0  freq=8
id=tcp_port_scan       ip=192.168.1.110   dos_id=1  exp=175   pps=0  freq=0
id=ip_src_session      ip=192.168.1.110   dos_id=1  exp=5649  pps=0  freq=30
id=udp_src_session     ip=192.168.1.110   dos_id=1  exp=5649  pps=0  freq=22
```

Which IP addresses are included in the output of this command?

- A. Those whose traffic matches a DoS policy.
- B. Those whose traffic matches an IPS sensor.
- C. Those whose traffic exceeded a threshold of a matching DoS policy.
- D. Those whose traffic was detected as an anomaly by an IPS sensor.



Correct Answer: A

QUESTION 3

View these partial outputs from two routing debug commands:

```
# get router info kernel
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.1.254
dev=2 (port1)
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.2.254
dev=3 (port2)
tab=254 vf=0 scope=253 type=1 proto=2 prio=0 0.0.0.0/0.0.0.0/0->10.0.1.0/24 pref=10.0.1.254 gwy=0.0.0.0
dev=4 (port3)
# get router info routing-table all
s* 0.0.0.0/0 [10/0] via 10.200.1.254, port1
    [10/0] via 10.200.2.254, port2, [10/0]
C 10.0.1.0/24 is directly connected, port3
C 10.200.1.0/24 is directly connected, port1
C 10.200.2.0/24 is directly connected, port2
```

Which outbound interface will FortiGate use to route web traffic from internal users to the Internet?

- A. Both port1 and port2
- B. port3
- C. port1
- D. port2

Correct Answer: C

QUESTION 4

View the exhibit, which contains a partial web filter profile configuration, and then answer the question below.

Which action will FortiGate take if a user attempts to access www.dropbox.com, which is categorized as File Sharing and Storage?

- A. FortiGate will exempt the connection based on the Web Content Filter configuration.
- B. FortiGate will block the connection based on the URL Filter configuration.
- C. FortiGate will allow the connection based on the FortiGuard category based filter configuration.
- D. FortiGate will block the connection as an invalid URL.

Correct Answer: B



QUESTION 5

A FortiGate device has the following LDAP configuration:

```
config user ldap
  edit "WindowsLDAP"
    set server "10.0.1.10"
    set cnid "cn"
    set dn "cn=Users, dc=trainingAD, dc=training, dc=lab"
    set type regular
    set username "dc=trainingAD, dc=training, dc=lab"
    set password xxxxxxxx
  next
end
```

The administrator executed the ``dsquery\'` command in the Windows LDAP server 10.0.1.10, and got the following output: `>dsquery user -samid administrator "CN=Administrator, CN=Users, DC=trainingAD, DC=training, DC=lab"`
Based on the output, what FortiGate LDAP setting is configured incorrectly?

- A. cnid.
- B. username.
- C. password.
- D. dn.

Correct Answer: B

<https://kb.fortinet.com/kb/viewContent.do?externalId=FD37516>

[NSE7_EFW-6.2 PDF Dumps](#)

[NSE7_EFW-6.2 Practice Test](#)

[NSE7_EFW-6.2 Braindumps](#)