



NSE7_EFW-6.2^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.2

Pass Fortinet NSE7_EFW-6.2 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_efw-6-2.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Examine the output of the 'diagnose debug rating' command shown in the exhibit; then answer the question below.

```
# diagnose debug rating
Locale      : english
License     : Contract
Expiration  : Wed Mar 27 17:00:00 20xx
== Server List (Mon Apr 16 15:32:55 20xx) ==
IP          Weight  RTT   Flags  TZ   Packets  Curr Lost  Total Lost
69.195.205.101 10      45    -5     -5   262432   0          846
69.195.205.102 10      46    -5     -5   329072   0          6806
209.222.147.43 10      75    -5     -5   71638    0          275
96.45.33.65    20      71    -8     -8   36875    0          92
208.91.112.196 20      103   DI     -8   34784    0          1070
208.91.112.198 20      107   D      -8   35170    0          1533
80.85.69.41    60      144    0      0    33728    0          120
62.209.40.73   71      226    1      1    33797    0          192
121.111.236.180 150     197    9      9    33754    0          145
69.195.205.103 45      44     F     -5   26410    26226     26227
```

Which statement are true regarding the output in the exhibit? (Choose two.)

- A. There are three FortiGuard servers that are not responding to the queries sent by the FortiGate.
- B. The TZ value represents the delta between each FortiGuard server's time zone and the FortiGate's time zone.
- C. FortiGate will send the FortiGuard queries to the server with highest weight.
- D. A server's round trip delay (RTT) is not used to calculate its weight.

Correct Answer: BC

QUESTION 2

Examine the following partial output from a sniffer command; then answer the question below.

```
# diagnose sniff packet any 'icmp' 4
interfaces= [any]
filters = [icmp]
2.101199 wan2 in 192.168.1.110-> 4.2.2.2: icmp: echo request
2.101400 wan1 out 172.17.87.16-> 4.2.2.2: icmp: echo request
.....
2.123500 wan2 out 4.2.2.2-> 192.168.1.110: icmp: echo reply
244 packets received by filter
5 packets dropped by kernel
```



What is the meaning of the packets dropped counter at the end of the sniffer?

- A. Number of packets that didn't match the sniffer filter.
- B. Number of total packets dropped by the FortiGate.
- C. Number of packets that matched the sniffer filter and were dropped by the FortiGate.
- D. Number of packets that matched the sniffer filter but could not be captured by the sniffer.

Correct Answer: D

<https://kb.fortinet.com/kb/documentLink.do?externalID=11655>

QUESTION 3

View the exhibit, which contains the output of a real-time debug, and then answer the question below.

```
# diagnose debug application urlfilter -1
# diagnose debug enable

msg="received a request /tmp/.ipsengine_498_0_0.url.socket, addr_len=37:
d=www.fortinet.com:80
id=83, vfname='rcot', vfid=0, profile='default', type=0, client=10.0.1.10,
url_source=1, url=/"
msg="Found it in cache. URL cat=52" IP cat=52user="N/A" src=10.0.1.10
sport=60348 dst=66.171.121.44 dport=80 service="http" hostname="
www.fortinet.com" url=/" matchType=prefix
action=10(ftgd-block) wf-act=3(BLOCK) user="N/A" src=10.0.1.10 sport=60348
dst=66.171.121.44
dport=80 service="http" cat=52 cat desc="Information Technology"
hostname="fortinet.com"
url=/"
```

Which of the following statements is true regarding this output? (Choose two.)

- A. This web request was inspected using the root web filter profile.
- B. FortiGate found the requested URL in its local cache.
- C. The requested URL belongs to category ID 52.
- D. The web request was allowed by FortiGate.

Correct Answer: BC

QUESTION 4

Examine the following routing table and BGP configuration; then answer the question below.



```
#get router info routing-table all
*0.0.0.0/0 [10/0] via 10.200.1.254, port1
C10.200.1.0/24 is directly connected, port1
S192.168.0.0/16 [10/0] via 10.200.1.254, port1
# show router bgp
config router bgp
set as 65500
set router-id 10.200.1.1
set network import check enable
set ebgp-multipath disable
config neighbor
edit "10.200.3.1"
set remote-as 65501
next
end
config network
edit1
```

The BGP connection is up, but the local peer is NOT advertising the prefix 192.168.1.0/24. Which configuration change will make the local peer advertise this prefix?

- A. Enable the redistribution of connected routers into BGP.
- B. Enable the redistribution of static routers into BGP.
- C. Disable the setting network-import-check.
- D. Enable the setting ebgp-multipath.

Correct Answer: C

QUESTION 5

Examine the partial output from the IKE real time debug shown in the exhibit; then answer the question below.

Why didn't the tunnel come up?

- A. IKE mode configuration is not enabled in the remote IPsec gateway.
- B. The remote gateway's Phase-2 configuration does not match the local gateway's phase-2 configuration.
- C. The remote gateway's Phase-1 configuration does not match the local gateway's phase-1 configuration.
- D. One IPsec gateway is using main mode, while the other IPsec gateway is using aggressive mode.

Correct Answer: C



VCE & PDF

PassApply.com

https://www.passapply.com/nse7_efw-6-2.html

2024 Latest passapply NSE7_EFW-6.2 PDF and VCE dumps Download

[NSE7_EFW-6.2 VCE
Dumps](#)

[NSE7_EFW-6.2 Study
Guide](#)

[NSE7_EFW-6.2 Exam
Questions](#)