



NSE7_EFW-6.4^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.4

Pass Fortinet NSE7_EFW-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_efw-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Examine the partial output from the IKE real time debug shown in the exhibit; then answer the question below.

Why didn't the tunnel come up?

- A. IKE mode configuration is not enabled in the remote IPsec gateway.
- B. The remote gateway's Phase-2 configuration does not match the local gateway's phase- 2 configuration.
- C. The remote gateway's Phase-1 configuration does not match the local gateway's phase- 1 configuration.
- D. One IPsec gateway is using main mode, while the other IPsec gateway is using aggressive mode.

Correct Answer: C

QUESTION 2

Refer to the exhibit, which shows a FortiGate configuration.



```
config system fortiguard
  set protocol udp
  set port 8888
  set load-balance-servers 1
  set auto-join-forticloud enable
  set update-server-location any
  set sandbox-region ""
  set fortiguard-anycast disable
  set antispam-force-off disable
  set antispam-cache enable
  set antispam-cache-ttl 1800
  set antispam-cache-mpercent 2
  set antispam-timeout 7
  set webfilter-force-off enable
  set webfilter-cache enable
  set webfilter-cache-ttl 3600
  set webfilter-timeout 15
  set sdns-server-ip "208.91.112.220"
  set sdns-server-port 53
  unset sdns-options
  set source-ip 0.0.0.0
  set source-ip6 ::
  set proxy-server-ip 0.0.0.0
  set proxy-server-port 0
  set proxy-username ""
  set ddns-server-ip 0.0.0.0
  set ddns-server-port 443
end
```

An administrator is troubleshooting a web filter issue on FortiGate. The administrator has configured a web filter profile and applied it to a policy; however, the web filter is not inspecting any traffic that is passing through the policy.

What must the administrator change to fix the issue?

- A. The administrator must increase webfilter-timeout.
- B. The administrator must disable webfilter-force-off.
- C. The administrator must change protocol to TCP.
- D. The administrator must enable fortiguard-anycast.

Correct Answer: D

Reference: <https://docs.fortinet.com/document/fortigate/6.4.5/cli-reference/109620/config-systemfortiguard>



QUESTION 3

A corporate network allows Internet Access to FSSO users only. The FSSO user student does not have Internet access after successfully logged into the Windows AD network. The output of the `diagnose debug authd fssolist` command does not show student as an active FSSO user. Other FSSO users can access the Internet without problems. What should the administrator check? (Choose two.)

- A. The user student must not be listed in the CA's ignore user list.
- B. The user student must belong to one or more of the monitored user groups.
- C. The student workstation's IP subnet must be listed in the CA's trusted list.
- D. At least one of the student's user groups must be allowed by a FortiGate firewall policy.

Correct Answer: AD

<https://kb.fortinet.com/kb/documentLink.do?externalID=FD38828>

QUESTION 4

An administrator cannot connect to the GIU of a FortiGate unit with the IP address 10.0.1.254. The administrator runs the debug flow while attempting the connection using HTTP. The output of the debug flow is shown in the exhibit:

```
# diagnose debug flow filter port 80
# diagnose debug flow trace start 5
# diagnose debug enable

id=20085 trace_id=5 msg="vd-root received a packet(proto=6,
10.0.1.10:57459->10.0.1.254:80) from port3. flag [S], seq 3190430861, ack
0, win 8192"
id=20085 trace_id=5 msg="allocate a new session-0000008c"
id=20085 trace_id=5 msg="iprope_in_check() check failed on policy 0, drop"
```

Based on the error displayed by the debug flow, which are valid reasons for this problem? (Choose two.)

- A. HTTP administrative access is disabled in the FortiGate interface with the IP address 10.0.1.254.
- B. Redirection of HTTP to HTTPS administrative access is disabled.
- C. HTTP administrative access is configured with a port number different than 80.
- D. The packet is denied because of reverse path forwarding check.

Correct Answer: AC

QUESTION 5

View the exhibit, which contains the partial output of an IKE real-time debug, and then answer the question below.



```
ike 0: comes 10.0.0.2:500-> 10.0.0.1:500, ifindex-7...
ike 0: IKEV1 exchange-Aggressive id-baf47d0988e9237f/2f405ef3952f6fda len 430
ike 0: in
BAF47D0988E9237F2F405EF3952F6FDA0110040000000000000001AE0400003C0000000100000001000000300101000
ike 0: RemoteSite:4: initiator: aggressive mode get 1st response
ike 0: RemoteSite:4: VID RFC 3947 4A131C81070358455C5728F20E95452F
ike 0: RemoteSite:4: VID DPD AFCAD71368A1F1c96B8696FC77570100
ike 0: RemoteSite:4: VID FORTIGATE 8299031757A36082C6A621DE000502D7
ike 0: RemoteSite:4: peer is FortiGate/FortiOS (v6 b932)
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3C0000000
ike 0: RemoteSite:4: received peer identifier FQDN 'remote'
ike 0: RemoteSite:4: negotiation result
ike 0: RemoteSite:4: proposal id = 1:
ike 0: RemoteSite:4:   protocol id - ISAKMP:
ike 0: RemoteSite:4:   trans_id - KEY_IKE.
ike 0: RemoteSite:4:   encapsulation - IKE/none
ike 0: RemoteSite:4:   type=OAKLEY_ENCRYPT_ALG, val=AES_CBC, key-len=128
ike 0: RemoteSite:4:   type=OAKLEY_HASH_ALG, val-SHA
ike 0: RemoteSite:4:   type=AUTH_METHOD, val=PRESHARED_KEY.
ike 0: RemoteSite:4:   type=OAKLEY_GROUP, val=MODF1024.
ike 0: RemoteSite:4: ISAKMP SA lifetime=86400
ike 0: RemoteSite:4: ISAKMP SA baf47d0988e9237f/2f405ef3952f6fda key
16:B25B6C9384D8BDB24E3DA3DC90CF5E73
ike 0: RemoteSite:4: PSK authentication succeeded
ike 0: RemoteSite:4: authentication OK
ike 0: RemoteSite:4: add INITIAL-CONTACT
ike 0: RemoteSite:4: enc
BAF47D0988E9237F2F405EF3952F6FDA08100401000000000000080140000181F2E48BFD8E9D603F
ike 0: RemoteSite:4: out
BAF47D0988E9237F2F405EF3952F6FDA0810040100000000000008c2E3FC9BA061816A396F009A12
ike 0: RemoteSite:4: sent IKE msg (agg_12send) : 10.0.0.1:500 ->10.0.0.2:500, len-140, id-
baf47d0988e9237f/2
ike 0: RemoteSite:4: established IKE SA baf47d0988e9237f/2f405ef3952f6fda
```

Which statements about this debug output are correct? (Choose two.)

- A. The remote gateway IP address is 10.0.0.1.
- B. It shows a phase 1 negotiation.
- C. The negotiation is using AES128 encryption with CBC hash.
- D. The initiator has provided remote as its IPsec peer ID.

Correct Answer: BD

[Latest NSE7_EFW-6.4 Dumps](#)

[NSE7_EFW-6.4 VCE Dumps](#)

[NSE7_EFW-6.4 Practice Test](#)