



NSE7_SDW-6.4^{Q&As}

Fortinet NSE 7 - SD-WAN 6.4

Pass Fortinet NSE7_SDW-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_sdw-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What are two reasons why it is effective to implement the internet service database (ISDB) in an SD-WAN rule? (Choose two)

- A. The ISDB is dynamically updated and reduces administrative overhead.
- B. The ISDB applies rules to traffic from specific sources, based on application type.
- C. The ISDB requires application control to maintain signatures and perform load-balancing.
- D. The ISDB contains the IP addresses and port ranges of well-known destinations.

Correct Answer: AD

QUESTION 2

Refer to the exhibit.

```
PortiGate # diagnose firewall shaper traffic-shaper list name VoIP_Shaper
name VoIP_Shaper
maximum-bandwidth 6250 KB/sec
guaranteed-bandwidth 2500 KB/sec
current-bandwidth 93 KB/sec
priority 2
overhead 0
tos ff
packets dropped 0
bytes dropped 0
```

Which two statements about the debug output are true? (Choose two)

- A. The debug output shows per-IP shaper values and real-time readings.
- B. FortiGate provides statistics and reading based on historical traffic logs.
- C. Traffic being controlled by the traffic shaper is under 100 KB/s.
- D. This traffic shaper drops traffic that exceeds the set limits.

Correct Answer: CD

QUESTION 3

Which feature enables SD-WAN to combine IPsec VPN dynamic shortcut tunnels between spokes and a static tunnel to the hub?

- A. ADVPN



- B. GRE
- C. SSLVPN
- D. OCVPN

Correct Answer: A

QUESTION 4

Which diagnostic command can you use to show interface-specific SLA logs for the last 10 minutes?

- A. diagnose sys sdwan log
- B. diagnose sys sdwan health-check
- C. diagnose sys sdwan intf-sla-log
- D. diagnose sys sdwan sla-log

Correct Answer: D

diagnose sys sdwan intf-sla-log -> shows only bandwidth utilization
diagnose sys sdwan sla-log -> shows packet-loss, latency, jitter, MOS

QUESTION 5

What are the two minimum configuration requirements for an outgoing interface to be selected once the SD-WAN logical interface is enabled? (Choose two)

- A. Specify outgoing interface routing cost.
- B. Configure SD-WAN rules interface preference.
- C. Select SD-WAN balancing strategy.
- D. Specify incoming interfaces in SD-WAN rules.

Correct Answer: AB

[NSE7_SDW-6.4 VCE Dumps](#)

[NSE7_SDW-6.4 Exam Questions](#)

[NSE7_SDW-6.4 Braindumps](#)