



NSE7_SDW-7.0^{Q&As}

Fortinet NSE 7 - SD-WAN 7.0

Pass Fortinet NSE7_SDW-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/nse7_sdw-7-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Refer to exhibits.

Exhibit A Exhibit B

Edit Policy

| | |
|--------------------|---|
| Name | Internet Access |
| Incoming interface | port3 |
| Outgoing interface | virtual-wan link |
| Source | all + x |
| Destination | all + x |
| Schedule | always |
| Service | ALL + x |
| Action | <input checked="" type="checkbox"/> ACCEPT <input type="checkbox"/> DENY |
| Inspection Mode | <input checked="" type="checkbox"/> Flow-based <input type="checkbox"/> Proxy-based |

Firewall / Network Options

| | |
|-----------------------|---|
| NAT | <input checked="" type="checkbox"/> |
| IP Pool Configuration | <input checked="" type="checkbox"/> Use Outgoing Interface Address <input type="checkbox"/> Use Dynamic |
| Preserve Source Port | <input type="checkbox"/> |
| Protocol Options | <input checked="" type="checkbox"/> PROT default |



Exhibit A | **Exhibit B**

Edit Traffic Shaping Policy

Name:

Status: Enabled Disabled

Comments: 0/255

If Traffic Matches:

Source:

Destination:

Schedule:

Service:

Application:

URL Category:

Then:

Action: Apply Shaper Assign Shaping Class ID

Outgoing interface:

Shared shaper:

Exhibit A shows the firewall policy and exhibit B shows the traffic shaping policy.

The traffic shaping policy is being applied to all outbound traffic; however, inbound traffic is not being evaluated by the shaping policy.

Based on the exhibits, what configuration change must be made in which policy so that traffic shaping can be applied to inbound traffic?



- A. Create a new firewall policy, and the select the SD-WAN zone as Incoming Interface.
- B. In the traffic shaping policy, select Assign Shaping Class ID as Action.
- C. In the firewall policy, select Proxy-based as Inspection Mode.
- D. In the traffic shaping policy, enable Reverse shaper, and then select the traffic shaper to use.

Correct Answer: D

QUESTION 2

In the default SD-WAN minimum configuration, which two statements are correct when traffic matches the default implicit SD-WAN rule? (Choose two)

- A. Traffic has matched none of the FortiGate policy routes.
- B. Matched traffic failed RPF and was caught by the rule.
- C. The FIB lookup resolved interface was the SD-WAN interface.
- D. An absolute SD-WAN rule was defined and matched traffic.

Correct Answer: AC

QUESTION 3

Refer to the exhibit.

```
config system virtual-wan-link
  set status enable
  set load-balance-mode source-ip-based
  config members
    edit 1
      set interface "port1"
      set gateway 100.64.1.254
      set source 100.64.1.1
      set cost 15
    next
    edit 2
      set interface "port2"
      set gateway 100.64.2.254
      set priority 10
    next
  end
end
```

Based on the output shown in the exhibit, which two criteria on the SD-WAN member configuration can be used to



select an outgoing interface in an SD-WAN rule? (Choose two.)

- A. Set priority 10.
- B. Set cost 15.
- C. Set load-balance-mode source-ip-ip-based.
- D. Set source 100.64.1.1.

Correct Answer: AB

QUESTION 4

Refer to the exhibit.

```
config system sdwan
  set status enable
  set load-balance source-dest-ip-based
  config zone
    edit "virtual-wan-link"
    next
    edit "SASE"
    next
    edit "underlay"
    next
  end
  config members
    edit 1
      set interface "port1"
      set zone "underlay"
      set gateway 192.2.0.2
    next
    edit 2
      set interface "port2"
      set zone "underlay"
      set gateway 192.2.0.10
    next
  end
  ...
end
```

Which algorithm does SD-WAN use to distribute traffic that does not match any of the SD-WAN rules?



- A. All traffic from a source IP to a destination IP is sent to the same interface.
- B. All traffic from a source IP is sent to the same interface.
- C. All traffic from a source IP is sent to the most used interface.
- D. All traffic from a source IP to a destination IP is sent to the least used interface.

Correct Answer: A

QUESTION 5

What would best describe the SD-WAN traffic shaping mode that bases itself on a percentage of available bandwidth?

- A. Per-IP shaping mode
- B. Reverse policy shaping mode
- C. Interface-based shaping mode
- D. Shared policy shaping mode

Correct Answer: C

SD-WAN 6.4.5 Study Guide. pg 124

[NSE7_SDW-7.0 PDF Dumps](#)

[NSE7_SDW-7.0 Practice Test](#)

[NSE7_SDW-7.0 Braindumps](#)