



# PCSAE<sup>Q&As</sup>

Palo Alto Networks Certified Security Automation Engineer

## Pass Palo Alto Networks PCSAE Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/pcsae.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Palo Alto Networks Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

An engineer deployed two different instances of Active Directory for each organization site. As part of account enrichment use case, the engineer would like to delete a user from one specific site.

Which command will accomplish this?

- A. run ``ad-delete-user`` command with ``user-dn`` arg and `using-brand="Active Directory Query v2"`
- B. run ``ad-delete-user`` command with ``user-dn`` arg and `raw-response=true`
- C. run ``ad-delete-user`` command with ``user-dn`` arg and `ignore-outputs=true`
- D. run ``ad-delete-user`` command with ``user-dn`` arg and `using="Active Directory Query v2_instance_1"`

Correct Answer: A

---

### QUESTION 2

Which three options can be defined in the layout settings? (Choose three.)

- A. Set of fields to present
- B. Permission to view the tab based on ``Users``
- C. Permission to view the tab based on ``Roles``
- D. Delete built-in tabs including the war room
- E. Dynamic sections

Correct Answer: ACE

Reference: <https://docs.paloaltonetworks.com/cortex/cortex-xsoar/6-1/cortex-xsoar-admin/incidents/customize-incident-view-layouts/customize-incident-layouts.html>

---

### QUESTION 3

An engineer's organization system is registered in the following manner: . The engineer created a new indicator type for detecting systems using regex. The engineer would now like the username to be created as a separate ``User`` indicator automatically once a system is found.

What is the most efficient way for the engineer to achieve this?

- A. Create a custom indicator field named ``username`` and link it to the internal system indicator
- B. Change the reputation command for the internal system indicator type
- C. Create a new indicator type of the internal username and set a formatting script to extract only the username
- D. Create a new indicator type of the internal username and have the regex included on any string that has dash at the



beginning

Correct Answer: B

Reference: <https://docs.paloaltonetworks.com/cortex/cortex-xsoar/6-0/cortex-xsoar-threat-intel-management-guide/manage-indicators/understand-indicators/indicator-types/indicator-type-profile>

#### QUESTION 4

DRAG DROP

Match the appropriate action to the layout type.

Select and Place:

#### Answer Area

War Room	Drag answer here	View inputs and outputs of a playbook
Work Plan	Drag answer here	Execute a command
Incident Info	Drag answer here	View Incidents 'Similarity Scale'
Related Incidents	Drag answer here	Change incident fields

Correct Answer:



### Answer Area

War Room	Execute a command	
Work Plan	View inputs and outputs of a playbook	
Incident Info	Change incident fields	
Related Incidents	View Incidents 'Similarity Scale'	

#### QUESTION 5

What can be added to offload integration instance processing from the main server?

- A. Database node
- B. Application server
- C. Engine
- D. Development server

Correct Answer: A

[Latest PCSAE Dumps](#)

[PCSAE VCE Dumps](#)

[PCSAE Braindumps](#)