



# QSDA2019<sup>Q&As</sup>

Qlik Sense Data Architect Certification Exam - June 2019 Release

**Pass Qlik QSDA2019 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/qsgda2019.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Qlik Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A data architect plans to build an app that contains geographically diverse data that must be specific to user run-time selections. The source contains transactional data. The app must have minimal impact on already limited server resources.

Which approach should the data architect use?

- A. Loop and Reduce
- B. QVDs
- C. In-memory
- D. ODAG

Correct Answer: A

---

### QUESTION 2

A data architect needs to load Table\_A from an Excel file and sort the data by Field\_2. Which script should the data architect use?



A)

```
Temp:
LOAD
    Field_1,
    Field_2,
    Field_3
FROM [lib://Data/Table_A.xlsx]
(ooxml, embedded labels, table is Sheet1);

Table_A:
LOAD *
resident Temp Order by Field_2 asc;

drop Table Temp;
```

B)

```
Table_A:
LOAD *
Order by Field_2 asc;

LOAD
    Field_1,
    Field_2,
    Field_3
FROM [lib://Data/Table_A.xlsx]
(ooxml, embedded labels, table is Sheet1);
```

C)

```
Table_A:
LOAD
    Field_1,
    Field_2,
    Field_3
FROM [lib://Data/Table_A.xlsx]
(ooxml, embedded labels, table is Sheet1)
Order by Field_2 asc;
```



D)

```
Temp:
LOAD
    Field_1,
    Field_2,
    Field_3
FROM [lib://Data/Table_A.xlsx]
(xml, embedded labels, table is Sheet1);

NoConcatenate

Table_A:
LOAD *
resident Temp Order by Field_2 asc;
drop Table Temp;
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

### QUESTION 3

Multiple department fields in a dataset require a description. A data architect needs to add the department descriptions or a default value when the department does NOT have a description.

Which strategy should the data architect use to meet these requirements?

- A. ApplyMap with two parameters after the Mapping load
- B. Left Join between tables and Description.xlsx in every Department table
- C. Enter "Missing description" in the blank rows for Description.xlsx, then use Mapping Load
- D. ApplyMap with three parameters after the Mapping load

Correct Answer: A

### QUESTION 4

Refer to the exhibit.



OrderID	CustomerID	EmployeeID	ShipperID	FreightWeight	OrderDate
6571	4	16	2	43,48	2017-06-28
6570	79	13	2	29,2	2016-06-29
6569	79	45	2	79,17	2017-07-02
6568	4	33	2	43,41	2016-12-02
6567	79	19	1	23,2	2017-04-03
6566	34	45	2	66,54	2017-07-04
6565	4	13	2	49,18	2016-01-06
6564	34	19	1	43,89	2017-06-06
6563	34	13	2	22,56	2016-07-09
6562	4	32	2	33,98	2016-07-10

The data architect needs to create a KPI that displays the average amount of orders per customer. This aggregated field should be added to the existing orders table.

Which script should the data architect use?



A)

```
Orders:
LOAD
    OrderID,
    CustomerID,
    EmployeeID,
    ShipperID,
    FreightWeight,
    OrderDate
FROM [lib://Data/Orders.xlsx]
(ooxml, embedded labels, table is Sheet1);

Left Join(Orders)

LOAD
    CustomerID,
    Count(OrderID) AS NumberOfOrdersPerCustomer
Resident Orders
Group By CustomerID;
```

B)

```
Orders:
LOAD
    OrderID,
    CustomerID,
    EmployeeID,
    ShipperID,
    FreightWeight,
    OrderDate
FROM [lib://Data/Orders.xlsx]
(ooxml, embedded labels, table is Sheet1);

Left Join(Orders)

LOAD
    CustomerID,
    Count(OrderID) AS NumberOfOrdersPerCustomer
Resident Orders;
```



C)

```
Orders:
LOAD
    OrderID,
    CustomerID,
    EmployeeID,
    ShipperID,
    FreightWeight,
    OrderDate
FROM [lib://Data/Orders.xlsx]
(ooxml, embedded labels, table is Sheet1);

CustomerOrders:
LOAD
    CustomerID,
    Count(OrderID) AS NumberOfOrdersPerCustomer
Resident Orders
Group By CustomerID;
```

D)

```
Orders:
LOAD
    OrderID,
    CustomerID,
    EmployeeID,
    ShipperID,
    FreightWeight,
    OrderDate
FROM [lib://Data/Orders.xlsx]
(ooxml, embedded labels, table is Sheet1);

CustomerOrders:
LOAD
    CustomerID,
    Count(OrderID) AS NumberOfOrdersPerCustomer
Resident Orders
Group By;
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

## QUESTION 5

A data architect is developing an app that will generate QVDs for multiple business analysts. The field naming conventions on the source data are NOT business friendly. For every table loaded, multiple fields will require a name change. An Excel file is maintained centrally that lists all source data field names and the appropriate names as they should appear in the QVDs



Which strategy should the data architect use to meet these requirements?

- A. Use the Rename function and a mapping load
- B. Create master items using business-friendly names
- C. Use the Alias function and a mapping load
- D. Load in the Excel file as a data island and use the Peek function

Correct Answer: A

[Latest QSDA2019 Dumps](#)

[QSDA2019 Study Guide](#)

[QSDA2019 Exam Questions](#)