



VCS-273^{Q&As}

Administration of Veritas NetBackup 7.6.1 and NetBackup Appliances
2.6.1

Pass Veritas VCS-273 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/vcs-273.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veritas
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

In a NetBackup environment with only appliances, there is a mixture of 1GbE and 10GbE networks as well as Fibre channel SAN. Which two performance tuning scenarios result in optimized backup throughput? (Select two.)

- A. create a single bonded interface using all available interfaces, disable client-side deduplication throughout the environment, and enable network resiliency to improve network throughput
- B. create separate bonded interfaces from the available 1GbE and 10GbE interfaces and configure the Fibre Transport Media Server option to back up busy application servers
- C. create separate bonded interfaces from the available 1GbE and 10GbE interfaces, leverage network resiliency, and enable WAN optimization to improve network throughput
- D. create separate bonded interfaces from the available 1GbE and 10GbE interfaces and leverage client-side deduplication for all suitable LAN based clients
- E. create a single bonded interfaces from all the available interfaces and leverage client- side deduplication for all suitable LAN based clients

Correct Answer: BD

QUESTION 2

Which file contains LiveUpdate server configuration?

- A. pd.conf
- B. bp.conf
- C. nblu.conf
- D. vm.conf

Correct Answer: C

QUESTION 3

An administrator took Media Server, mediaA, offline for maintenance and set up a new Media Server, mediaB, with access to the previously backed up data. When restores are performed for data that was backed up by mediaA, the restores fail.

Which setting in the Host Properties must the administrator modify to allow successful restores?

- A. From the Master Server, run the bpimage command to change the name of the Media Server from mediaA to mediaB.



- B. Verify both Media Servers are set up in the Media Server Host Properties > Restore Failover section.
- C. In the BAR GUI, change the "Server to use for backup and restores" setting to MediaB.
- D. Verify both Media Servers are set up in the Master Server Host Properties > Restore Failover section.

Correct Answer: D

QUESTION 4

Which parameter in NetBackup Management > Host Properties must be modified to change the logging level to 5 for client1.domain?

- A. Master Servers > [master_server_name] > Logging > Global logging level
- B. Clients > [client_name] > Logging > Global logging level
- C. Master Servers > [master_server_name] > Logging > Enable robust logging
- D. Clients > [client_name] > Logging > Enable robust logging

Correct Answer: B

QUESTION 5

An administrator runs the following command on the Master Server to test connectivity to a client:

```
bptestbpcd -client clientA
```

The administrator receives the following message:

bptestbpcd main: Function ConnectToBPCD (clientA) failed: 25 cannot connect on socket Which two reasons may cause the error message? (Select two.)

- A.
an incorrect entry for the Master Server in the client\\s hosts file
- B.
the NetBackup processes on the client are stopped
- C.
the Master Server is unknown to the client
- D.



an incorrect entry for the client in the Master Server\\s hosts file

E.

vnetd is stopped on the Master Server

Correct Answer: BD

[VCS-273 PDF Dumps](#)

[VCS-273 Practice Test](#)

[VCS-273 Exam Questions](#)