



500-920^{Q&As}

Cisco Data Center Unified Computing Infrastructure Troubleshooting
(DCITUC)

Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-920.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which two components are required when the integration of Cisco UCS C-series servers within a Cisco UCS Manager Direct Connect mode? (Choose two)

- A. Compatible Cisco Nexus Fabric Extenders
- B. Cisco Management Controller
- C. Compatible UCS VIC adapter installed via the server's PCIe or MLOM slot
- D. Compatible UCS 6200 or 6300 Fabric Interconnects
- E. Compatible Cisco UCS Manager version

Correct Answer: CD

QUESTION 2

In Cisco UCS, there are several interfaces involved on the packet path from the vNIC through the adapter, IOM to finally reach Pi

Which is the order of those interfaces, starting from the vNIC?

- A. VIF, UIF, HIF, SIF NIF
- B. VIF, UIF, HIF, NIF SIF
- C. HIF, NIF, UIF, VIF SIF
- D. HIF, SIF, VIF, UIF NIF

Correct Answer: A

QUESTION 3

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server's BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server's BIOS
- D. Enable Quiet Boot on the Server's Service Profile
- E. Disable Fast Boot on the Server's Service Profile



Correct Answer: D

QUESTION 4

Which statement is true when using SPAN for Fibre Channel (FC) Traffic?

- A. FC port on Cisco UCS 6238UP can be used as a SPAN source
- B. When defining FC uplink port as the SPAN destination, system will automatically stop using that port as an uplink port
- C. Any port can be used as a SPAN destination port Even if it is defined as Eth uplink port it will be automatically converted to FC uplink port
- D. For FC SPAN sessions we do not have to specifically enable the monitoring session

Correct Answer: A

QUESTION 5

After installing a new UCS M4 server, which two Cisco Integrated Management Controller connectivity options do you have? (Choose two)

- A. XML API Access
- B. Web Access
- C. In-band Access
- D. SNMP
- E. Out-of-Band Access

Correct Answer: AC

QUESTION 6

Which two statements describes connecting the IO Modules in the UCS chassis to the Fabric interconnects? (Choose two)

- A. Connect FI-A to the IOM B of each chassis
- B. Connect FI-B to IOM A and IOM B in each chassis
- C. Connect FI-A to the IOM A of each chassis
- D. Connect FI-A to IOM A and IOM B in each chassis
- E. Connect FI-B to the IOM A of each chassis
- F. Connect FI-B to the IOM B of each chassis



Correct Answer: ACF

QUESTION 7

When it comes to pinning vNIC traffic from a UCS Server to the Fabric Interconnect uplink what configuration can you perform?

- A. You can configure Automatic Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the other Fabric Interconnect
- B. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the other Fabric Interconnect
- C. You can configure Automatic Uplink Pinning. If an uplink interface fails on one Fabric Interconnect the server will fail to the matching uplink on the other Fabric Interconnect
- D. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the same Fabric Interconnect
- E. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect the server will fail to the matching uplink on the other Fabric Interconnect

Correct Answer: A

QUESTION 8

The UCS Chassis Discovery Policy has been set to four and a new chassis is connected with two links What is the resulting chassis recognition action?

- A. The chassis will not be recognized
- B. The Chassis Discovery Policy will automatically reset to two links, since it always tracks the physical connections
- C. The chassis will be recognized and both links will be active
- D. The chassis will be recognized but only one of the links will be active.

Correct Answer: A

QUESTION 9

Which two interfaces allow access to Cisco UCS Manager? (Choose two)

- A. Cisco KVM
- B. Cisco UCS Manager XML API
- C. Cisco IMC
- D. Cisco UCS Manager GUI



Correct Answer: BD

QUESTION 10

What is the likely cause of an intermittent SAN Boot fails?

- A. Misconfigured SAN boot target in the boot policy of the service profile
- B. LUN ID Mismatch
- C. FCoE used instead of FC
- D. Wrong boot order in the service profile

Correct Answer: A

[500-920 PDF Dumps](#)

[500-920 VCE Dumps](#)

[500-920 Practice Test](#)