



E20-377^{Q&As}

RecoverPoint/SE Specialist Exam for Implementation Engineers

Pass EMC E20-377 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/e20-377.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which Solutions Enabler daemon provides for centralized gatekeeper device management for all applications requiring access to Symmetrix arrays?

- A. Base daemon (storapid)
- B. GNS daemon (storgnsd)
- C. RDF daemon (storrdfd)
- D. Event daemon (storevntd)

Correct Answer: A

QUESTION 2

With the DMX-3 and DMX4, where is the VCM database stored?

- A. Symmetrix Logical Volume
- B. Symmetrix File System
- C. Symmetrix Virtual Device
- D. Symmetrix VCM Device

Correct Answer: B

QUESTION 3

During the testing of an Open Respirator implementation the create operation failed. One of the lines in the SYMAP1 log file has the following entry SANCOPY_DEV_TARGET_TOO SMALL Which circumstance could lead to such an error?

- A. Pull operation to a larger control device
- B. Push operation from a larger control device
- C. Push operation from smaller control device
- D. Pull operation to a smaller control device

Correct Answer: B

QUESTION 4

A customer wants to perform SRDF operations, using the Consistency Exempt flag, on a subset of devices in an SRDF/A group. Which SRDF operation is allowed?



- A. Failover
- B. Suspend
- C. Split
- D. Restore

Correct Answer: B

QUESTION 5

A SMC user must have the ability to create new SMC users and assign permission. This user should not have any Symmetric configuration or replication privileges.

Which role should be assigned to this user?

- A. SecurityAdmin
- B. Auditor
- C. Admin
- D. StorageAdmin

Correct Answer: D

QUESTION 6

When the first device added to a thin pool RAID, which other types of protected devices can be added to the same thin pool?

- A. RAID 5
- B. RAID 1
- C. RAID 6
- D. Any RAID type

Correct Answer: B

QUESTION 7

What is an advantage of using thin provisioning?

- A. When the provisioning volume also protected with SRDF, no mirror positions would be used.
- B. Thin provisioning presents an application with more capacity than is physically allocated.



- C. Symmetrix Optimizer automatically tunes, monitors, analyzers, and migrate thin volumes to maintain optimal performance.
- D. The provisioning will help meet service-level requirements while providing powerful local-replication Capabilities.

Correct Answer: B

QUESTION 8

When an unconfigured device has to be added to a V-Max, which locks are placed?

- A. Configuration and back-end
- B. Configuration and front-end device
- C. Director and back-end
- D. Front-end device and back-end device

Correct Answer: A

QUESTION 9

TimeFinder/Snap virtual devices will be used as the control devices in an Open Replicator implementation. Which Open Replicator copy operation is supported?

- A. Cold Push
- B. Cold Pull
- C. Hot Push
- D. Hot Pull

Correct Answer: A

QUESTION 10

What is required when the symdev list command shows the TEMEVs (!?) are in a Not Ready state?

- A. Must be part of the default pool
- B. Must be mapped to a front-end port
- C. Must create an extent that is 12 tracks
- D. Must be bound to a thin pool

Correct Answer: D



QUESTION 11

What is the result of performing a TimeFinder/Mirror consistent split operation against a device group?

- A. All BCV devices in the group are consistent point-in-time copies.
- B. All standard devices in the group are consistent point-in-time copies.
- C. BCV devices are write-disabled and ready for synchronization with standard devices.
- D. All standard devices are write-disabled and ready for synchronization with BCV devices.

Correct Answer: A

QUESTION 12

Open Replicator will be used to move data from a Symmetrix V-max array to a CLARiiON array. The CLARiiON array has NOT been discovered by the host on which Open Replicator commands are issued. Which information has to be specified in the Open Replicator device File?

- A. Symdev=arrayid device clardev=arrayid: CLARiiON device WWN
- B. symdev=arrayed:device www=CLARiiON device WWN
- C. symdev= arrayid device clardev=arrayid device
- D. www=Symmetrix device WWN WWN=CLARiiON device WWN

Correct Answer: B

QUESTION 13

Which replication operations are supported by the Symmetrix Management Console?

- A. Open Replicator, SRDF/A, and SRDF/S
- B. SRDF/Star, TimeFinder/Clone, and TimeFinder/Snap
- C. Open Replicator, SRDF/Star, and TimeFinder/Snap
- D. SRDF/A, SRDF/S, and SRDF/Star

Correct Answer: A

QUESTION 14

What is another possible scheme for RAID 6 for a Symmetric V-max besides 6+2?

- A. 7+2
- B. 14+2



C. 3+2

D. 8+2

Correct Answer: B

QUESTION 15

When installing Solutions Enabler what are the core components that must be installed?

A. CORE, JNI, SQL, STORBASE, STORFULL

B. SYMRECOVER, SYMCLI, SRMBASE, SQL, UDB

C. CORE, SYMCLI, SRMBASE, STORBASE, STORFULL

D. ConfigChecker, SYMCLI, STORBASE, STORFULL

Correct Answer: C

[Latest E20-377 Dumps](#)

[E20-377 PDF Dumps](#)

[E20-377 Study Guide](#)