



# MA0-101<sup>Q&As</sup>

McAfee Certified Product Specialist - NSP

## Pass McAfee MA0-101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ma0-101.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by McAfee  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

What is the command to force the sensor out of Layer 2 Passthru mode?

- A. Layer2 mode off
- B. Layer2 mode on
- C. Layer2 mode assert
- D. Layer2 mode deassert

Correct Answer: D

---

#### QUESTION 2

Which of the following CLI commands removes trust between a sensor and manager, removes signatures and restores default port settings, but retains IP configuration?

- A. Resetconfig
- B. Deletesignatures
- C. Factotydefaults
- D. Deinstall

Correct Answer: A

---

#### QUESTION 3

Which of the following deployment modes is not included in standard NAC?

- A. System Health based NAC
- B. DHCP based NAC
- C. L2 based NAC
- D. L3 based NAC

Correct Answer: B

---

#### QUESTION 4

Which mode is used when certain hosts are located on the same network as a sensor and other hosts enter through a router or VPN?

- A. Mixed



- B. Hybrid
- C. Enforcement
- D. Prevention

Correct Answer: A

---

#### QUESTION 5

Which of the following CLI commands will not cause an automatic reboot of the Sensor?

- A. resetconfig
- B. delete signatures
- C. factorydefaults
- D. deinstall

Correct Answer: D

---

#### QUESTION 6

When creating policies, which of the following rule sets are available for selection within those policies?

- A. Only rule sets created using the Rule Set Editor
- B. Only rule sets imported from the Sensor
- C. Only rule sets created using the Rule Set Editor and Default rule sets
- D. Only Default Rule sets

Correct Answer: C

---

#### QUESTION 7

Which command is used to manually download signature tiles from the tftpsrvr when connectivity to the Manager is not available?

- A. Loadimage WORD
- B. Loadconfig WORD
- C. Loadconfiguration WORD
- D. Loadsigset WORD

Correct Answer: C

---



### QUESTION 8

A sensor will redirect the host to which of the following when McAfee NAC reports the Host status as "unmanaged with an Unknown Health Level"?

- A. Guest Client Portal
- B. NAC Client Portal
- C. Sensor Client Portal
- D. DNS Server Portal

Correct Answer: A

---

### QUESTION 9

Which step needs to be completed before a sensor can be configured?

- A. Sensor IP addressing must be set
- B. Sensor must be added to the Manager
- C. Sensor username and password must be set
- D. Sensor Gateway addressing must be set

Correct Answer: B

---

### QUESTION 10

McAfee recommends which of the following methods to cable the heartbeat connection of a sensor failover pair?

- A. direct fiber connection with specified monitoring ports
- B. direct copper connection using response ports
- C. switched fiber connection
- D. direct copper connection using failopen port

Correct Answer: A

---

### QUESTION 11

Identity Based Access Control cannot co-exist with which mode of NAC deployment on the same port?

- A. DHCP based NAC



- B. System Health based NAC
- C. L2 and L3 Deployment modes
- D. Mixed Deployment modes

Correct Answer: A

---

#### QUESTION 12

By default, sensors are configured to operate in which operating mode?

- A. In-line
- B. Tap
- C. SPAN
- D. Failover

Correct Answer: A

---

#### QUESTION 13

Which of the following options is the best practice to use if you need to edit all attacks with a specific severity number within an IPS policy?

- A. Use the Bulk Edit feature within the Policy Editor
- B. Create and run the appropriate database query
- C. Edit the attacks individually
- D. Use the Bulk Edit feature within the Reconnaissance Editor

Correct Answer: A

---

#### QUESTION 14

Which of the following are the methods used by NSP to recognize and react to Denial-of-Service (DoS) attacks?  
(Choose three)

- A. Blocking
- B. Shutting down the sensor
- C. Thresholds
- D. Self-learning
- E. Logging



F. DDoS attack tool with exploit signatures

Correct Answer: CDF

---

#### QUESTION 15

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

A. 8501

B. 8502

C. 8503

D. 8555

Correct Answer: C

[MA0-101 VCE Dumps](#)

[MA0-101 Study Guide](#)

[MA0-101 Braindumps](#)